

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LP: RW17 LNAV: RW17 CLIMB TO 3600 DIRECT BEFKO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 354.82 INBOUND. CHART FAS OBST: 1709 TREE 322657N/0984812W. WAAS CHANNEL # 77741 REFERENCE PATH ID: W17A OZXUD TO RW17: 3.50/48 CHART EASTLAND MUNI AWOS-3-3PT. LTP HAE: 412.1 M									
TRUSS		INIVE (TF) (FB) (RNP 2.00)			073.43 / 31.18			3600											
MQP VORTAC		WULED (TF) (FB) (RNP 2.00)			250.71 / 33.57			3600											
INIVE (IAF)		JIXIM (NOPT) (TF) (FB) (RNP 1.00)			084.77 / 6.01			3600											
WULED (IAF)		JIXIM (NOPT) (TF) (FB) (RNP 1.00)			264.92 / 8.00			3600											
JIXIM (IF/IAF)		OZXUD (TF) (FB) (RNP 1.00)			174.83 / 7.14			3100											
(SEE FORM 8260-10)																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N JIXIM, RT, 174.83 INBOUND, 3600 FT. IN LIEU OF PT (IAF) 3. FAC: 174.83 FAF: OZXUD DIST FAF TO MAP: 4.27 THLD: 4.27 4. MIN. ALT: JIXIM 3600, OZXUD 3100, CUMDA/2.70 NM TO RW17 2500 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW17 3500																MAG VAR: 7E		EPOCH YEAR: 1995	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @										
CATEGORY >>>>>	A			B			C			D			E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LP MDA	2040	1	572	2040	1	572	2040	1 5/8	572		NA								
LNAV MDA	2040	1	572	2040	1	572	2040	1 5/8	572		NA								
CIRCLING	2120	1	652	2120	1	652	2300	2 1/2	832		NA								
NOTES: CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON MQP VORTAC AIRWAY RADIALS 161 CW 330. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BRECKENRIDGE ALTIMETER SETTING. CHART NOTE: STRAIGHT-IN RWY 17 NA AT NIGHT, CIRCLING RWY 17 NA AT NIGHT.																			
CITY AND STATE		ELEVATION: 1468 TDZE: 1468			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP:							
EASTLAND, TX		AIRPORT NAME:					RNAV (GPS) RWY 17, ORIG-C					AMDT: ORIG-B							
		EASTLAND MUNI					7 DECEMBER 2017					DATED 12/11/2014							



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
OZXUD (FAF)	CUMDA/2.70 NM TO RW17 (TF) (FB) (RNP 0.30)		
CUMDA/2.70 NM TO RW17	RW17 (MAP) (TF) (FO) (RNP 0.30)	174.83 / 2.70	
RW17 (MAP)	1868 MSL (CA)		
1868 MSL	BEFKO (DF) (FO) (RNP 1.00)		3600

QUALITY
18
CHECKED

CITY AND STATE EASTLAND, TX	ELEVATION: 1468	TDZE: 1468	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG-C 7 DECEMBER 2017	SUP:	
	AIRPORT NAME:				AMDT:	ORIG-B
	EASTLAND MUNI				DATED:	12/11/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KETN
RUNWAY	RW17
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W17A
LTP/FTP LATITUDE	322508.6300N
LTP/FTP LONGITUDE	0984834.3500W
LTP/FTP ELLIPSOIDAL HEIGHT	+04121
FPAP LATITUDE	322339.3900N
FPAP LONGITUDE	0984837.7100W
THRESHOLD CROSSING HEIGHT (TCH)	00047.8
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.50
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

91FE8690

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+04406
FPAP ORTHOMETRIC HEIGHT	+04406

QUALITY
18
CHECKED

CITY AND STATE EASTLAND, TX	ELEVATION: 1468 TDZE: 1468 AIRPORT NAME: EASTLAND MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG-C 7 DECEMBER 2017	SUP:
				AMDT: ORIG-B
				DATED: 12/11/2014