

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
LIT VORTAC	HEPLU (FB)	013.70 / 57.49	3000	LPV: DA LNAV/VNAV: DA LNAV: RW08			
VILLO	CISOG (FB)	211.13 / 28.63	3000				
CISOG (IAF)	FIKIX (NOPT) (FB)	168.63 / 5.00	3000	CLIMB TO 3000 DIRECT NAPIC AND HOLD.			
HEPLU (IAF)	FIKIX (NOPT) (FB)	348.65 / 5.00	3000				
FIKIX (IF/IAF)	NICIN (FB)	078.64 / 6.01	2400	ADDITIONAL FLIGHT DATA: HOLD E, RT, 258.95 INBOUND. CHART FAS OBST: 472 TREE 354319N/0913946W CHART FAS OBST: 619 TREE 354313N/0914301W 1109 AAO 354106N/0914342W. 1259 AAO 354157N/0914625W. DISTANCE TO THLD FROM 250 HAT: 0.69 NM. CHART VDP AT 1.39 MILES TO RW08* *LNAV ONLY. WAAS CHANNEL # 97717 REFERENCE PATH ID: W08A LTP HAE: 110.3 M			
NICIN (FAF)	CUCAL/3.40 NM TO RW08 (FB)	078.73 / 2.49					
(SEE FORM 8260-10)							

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2.	HOLD W FIKIX, RT, 078.64 INBOUND, 3000 FT. IN LIEU OF PT (IAF)				
3.	FAC: 078.73	FAF: NICIN	DIST FAF TO MAP: 5.89		THLD: 5.89
4.	MIN. ALT: FIKIX 3000, NICIN 2400, CUCAL/3.40 NM TO RW08 1580*				
5.	DIST TO THLD FROM OM:		MM:	IM:	150 HAT: 100 HAT: GS ANT:
6.	MIN GS INCPT: 2400		GS ALT AT: NICIN 2400		OM: MM: IM:
7.	GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR				
8.	MSA FROM: RW08 2900				

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	713	1	250	713	1	250	713	1	250	713	1	250			
LNAV/VNAV DA	802	1 1/4	339	802	1 1/4	339	802	1 1/4	339	802	1 1/4	339			
LNAV MDA	940	1	477	940	1	477	940	1 1/4	477	940	1 1/2	477			
CIRCLING	980	1	515	980	1	515	980	1 1/2	515	1040	2	575			

NOTES:
 CHART NOTE: CIRCLING TO RWY 18-36 NA AT NIGHT.
 CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY.
 CHART NOTE: BARO-VNAV NA WHEN USING SEARCHY MUNI ALTIMETER SETTING.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F).
 (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE	ELEVATION: 465 TDZE: 463	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 7
BATESVILLE, AR	AIRPORT NAME: BATESVILLE RGNL		RNAV (GPS) RWY 8, AMDT 1A 18 NOV 2010	AMDT: 1
				DATED 06/03/2010

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
CUCAL/3.40 NM TO RW08	RW08 (MAP) (FO)	078.75 / 3.40	
RW08 (MAP)	713 MSL	078.75	
713 MSL	NAPIC (FO)		3000

NOTES, (CONT.):

CHART NOTE: DME/DME RNP-0.3 NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON LIT VORTAC AIRWAY RADIALS 288 CW 089.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: VDP NA WITH SEARCY ALTIMETER SETTING.

CHART NOTE: CIRCLING NA NW OF RWYS 8-26.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SEARCY MUNI ALTIMETER SETTING AND INCREASE ALL DA/MDA 100 FEET, INCREASE LPV, LNAV/VNAV ALL CATS, LNAV AND CIRCLING CATS C/D VISIBILITY 1/4 MILE.

QUALITY
CHECKED

CITY AND STATE
BATESVILLE, AR

ELEVATION: 465 TDZE: 463
AIRPORT NAME:
BATESVILLE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 8, AMDT 1A
18 NOV 2010

SUP: RNAV (GPS) RWY 7
AMDT: 1
DATED: 06/03/2010

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KBVX
RUNWAY RW08
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W08A
LTP/FTP LATITUDE 354323.0525N
LTP/FTP LONGITUDE 0913940.0710W
LTP/FTP ELLIPSOIDAL HEIGHT +01103
FPAP LATITUDE 354338.8400N
FPAP LONGITUDE 0913752.3700W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0920
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

DD31CADC

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K4
LTP ORTHOMETRIC HEIGHT +01378
FPAP ORTHOMETRIC HEIGHT +01378

QUALITY
5
CHECKED

CITY AND STATE BATESVILLE, AR	ELEVATION: 465 TDZE: 463 AIRPORT NAME: BATESVILLE RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 8, AMDT 1A 18 NOV 2010	SUP: RNAV (GPS) RWY 7
				AMDT: 1
				DATED: 06/03/2010

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KBVXK4FR08	AFIKIX	010FIKIXK4EA0EE	AR	HF		07860040	+	03000	18000		A	JS	I
SUSAP KBVXK4FR08	ALIT	010LIT K4D OV		IF					18000		A	JS	I
SUSAP KBVXK4FR08	ALIT	020HEPLUK4EA0E	A	020TF		01370575	+	03000			A	JS	I
SUSAP KBVXK4FR08	ALIT	030FIKIXK4EA0EE	B										

QUALITY
SERVICE

CITY AND STATE BATESVILLE, AR	ELEVATION: 465 AIRPORT NAME: BATESVILLE RGNL	TDZE: 463	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 8, AMDT 1A 18 NOV 2010	SUP: RNAV (GPS) RWY 7
					AMDT: 1
					DATED: 06/03/2010

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KBVXK4GRW08 0060020788 N35432305W091394007+0200 +0110300452000040150R 1

SUSAP KBVXK4PR08	RW08	001	0000W08A0N3543230525W09139400710+011030300N3543388400W09137523700106750920000400F400500DD31CADCI
SUSAP KBVXK4PR08	RW08	002E	+01378+01378LPV 97717 I

SUSAP KBVXK4SRW08 K4PG 0 18018002925 M 1

ELEVATION: 465 TDZE: 463
AIRPORT NAME:
BATESVILLE RGNL

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 8, AMDT 1A
18 NOV 2010

SUP:	RNAV (GPS) RWY 7
AMDT:	1
DATED:	06/03/2010