

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW30 CLIMB TO 2000 DIRECT NEYIB AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 126.90 INBOUND. FAS OBST: 404 AAO 281854N/0974427W. CHART 515 TOWER 281820N/0974235W. CHART KINGSVILLE 4 MOA. DISTANCE TO THLD FROM 255 HAT: 0.72 NM. CHART VDP AT 2.41 NM TO RW30* *LNAV ONLY. WAAS CHANNEL # 53741 REFERENCE PATH ID: W30A CHART CIRCLING ICON. LTP HAE: 47.5 M						
SINTO (IAF)		JOSUK (NOPT) (TF) (FB) (RNP 1.00)			009.33 / 8.81			2000								
KATLE (IAF)		JOSUK (NOPT) (TF) (FB) (RNP 1.00)			037.00 / 8.00			2000								
LOKKI (IAF)		JOSUK (NOPT) (TF) (FB) (RNP 1.00)			220.11 / 5.90			2000								
JOSUK (IF/IAF)		GUVLY (TF) (FB) (RNP 1.00)			307.05 / 6.02			2000								
GUVLY (FAF)		RW30 (MAP) (TF) (FO) (RNP 0.30)			306.99 / 5.38											
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SE JOSUK, RT, 307.05 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: 306.99 FAF: GUVLY DIST FAF TO MAP: 5.38 THLD: 5.38 4. MIN. ALT: JOSUK 2000, GUVLY 2000 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2000 GS ALT AT: GUVLY 2000 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 42.9 20:1 IS CLEAR 34:1 IS NOT CLEAR 8. MSA FROM: RW30 2100																
										MAG VAR: 4E			EPOCH YEAR: 2020			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @							
CATEGORY >>>>>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	517	1	255	517	1	255	517	1	255		NA					
LNAV/VNAV DA	540	1	278	540	1	278	540	1	278		NA					
LNAV MDA	1060	1	798	1060	1 1/4	798	1060	2 1/2	798		NA					
CIRCLING	1060	1	787	1060	1 1/4	787	1060	2 1/2	787		NA					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). @ CAT C 800-2 1/2 CHART NOTE: CIRCLING RWY 18 AND 36 NA AT NIGHT. CHART NOTE: RWY 30 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. PBN REQUIREMENTS NOTE: RNP APCH. (CONTINUED ON PAGE 2)																
CITY AND STATE		ELEVATION: 273 TDZE: 262			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
BEEVILLE, TX		AIRPORT NAME: BEEVILLE MUNI					RNAV (GPS) RWY 30, AMDT 1 24 MAY 2018				AMDT: ORIG-A					
											DATED 08/18/2016					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW30 (MAP)	517 MSL (CA)	306.99	
517 MSL	NEYIB (DF) (FO) (RNP 1.00)		2000

NOTES, (CONT.):

CHART PLANVIEW NOTE AT LOKKI: MAX 250 KIAS.
CHART PLANVIEW NOTE AT KATLE: MAX 250 KIAS.

CITY AND STATE
BEEVILLE, TX

ELEVATION: 273 TDZE: 262
AIRPORT NAME:
BEEVILLE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 30, AMDT 1
24 MAY 2018

SUP:
AMDT: ORIG-A
DATED: 08/18/2016

QUALITY
10
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE
BEEVILLE, TX

ELEVATION: 273 TDZE: 262
AIRPORT NAME:
BEEVILLE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 30, AMDT 1
24 MAY 2018

SUP: **QUALITY**
10
CHECKED
AMDT: ORIG-A
DATED: 08/18/2016

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KBEA
RUNWAY	RW30
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W30A
LTP/FTP LATITUDE	282127.9460N
LTP/FTP LONGITUDE	0974708.4525W
LTP/FTP ELLIPSOIDAL HEIGHT	+00475
FPAP LATITUDE	282226.4915N
FPAP LONGITUDE	0974824.7415W
THRESHOLD CROSSING HEIGHT (TCH)	00042.9
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1368
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

DCA6957C

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00744
FPAP ORTHOMETRIC HEIGHT	+00744

CITY AND STATE

BEEVILLE, TX

ELEVATION: 273

TDZE: 262

AIRPORT NAME:

BEEVILLE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 30, AMDT 1

24 MAY 2018

SUP:

AMDT:

DATED:

 QUALITY
10
CHECKED

ORIG-A

08/18/2016