

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA							
LARII (IAF)		JAAJJ (FB)		094.74 / 7.39			5000		CLIMB TO 1500 THEN CLIMBING LEFT TURN TO 3500 DIRECT TROYS AND HOLD.							
JAAJJ (IF)		BAZAR (FB)		094.82 / 3.45			4000									
BAZAR		SCHEL (FB)		094.86 / 4.37			2900									
SCHEL (FAF)		RW08L (MAP) (FO)		094.91 / 5.76												
RW08L (MAP)		1500 MSL		094.91			1500									
1500 MSL		TROYS (FO)					3500		ADDITIONAL FLIGHT DATA: HOLD N, RT, 185.00 INBOUND. CHART 1128 TREE 333836N/0842732W. DISTANCE TO THLD FROM 200 HAT: 0.47 NM. WAAS CHANNEL # 99300 REFERENCE PATH ID: W08B CODE APPROACH TRANSITION FROM JAAJJ. CODE FACF AT BAZAR. LTP HAE: 279.8 M							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. PROFILE STARTS AT LARII																
3. FAC: 094.91 FAF: _____ DIST FAF TO MAP: _____ THLD: _____																
4. MIN. ALT: LARII 5000, JAAJJ 5000, BAZAR 4000, SCHEL 2900																
5. DIST TO THLD FROM OM: 5.76 MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: 2900 GS ALT AT: SCHEL 2900 OM: _____ MM: _____ IM: _____																
7. GS ANGLE: 3.00 TCH: 49.9 34:1 IS NOT CLEAR																
8. MSA FROM: RW08L 3100										MAG VAR: 5W		EPOCH YEAR: 2015				
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X							
CATEGORY =====>		A			B			C			D			E		
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA		1215	2400	200	1215	2400	200	1215	2400	200	1215	2400	200			
LNAV/VNAV DA		1404	4500	389	1404	4500	389	1404	4500	389	1404	4500	389			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -7C (20F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: RADAR REQUIRED. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT. (SEE FORM 8260-10)																
CITY AND STATE  ATLANTA, GA		ELEVATION: 1026 TDZE: 1015 AIRPORT NAME:  HARTSFIELD - JACKSON ATLANTA INTL			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) PRM Y RWY 8L (SIMULTANEOUS CLOSE PARALLEL), ORIG  18 SEPTEMBER 2014						SUP: AMDT: NONE DATED			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):**

**CHART NOTE: FOR INOPERATIVE ALSF-2, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 1/4 MILES.**

**CHART NOTE: SIMULTANEOUS CLOSE PARALLEL APPROACH AUTHORIZED WITH ILS PRM AND RNAV PRM RWY 9L OR 9R OR 10, OR RWYS 9L AND 10, OR RWYS 9R AND 10.**

**CHART NOTE: DUAL VHF COMM REQUIRED.**

**CHART NOTE: SEE ADDITIONAL REQUIREMENTS ON AAUP.**

**CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.**

QUALITY  
4  
CHECKED

CITY AND STATE

ATLANTA, GA

**ELEVATION: 1026**

**TDZE: 1015**

AIRPORT NAME:

HARTSFIELD - JACKSON ATLANTA INTL

FACILITY  
IDENTIFIER:  
**RNAV**

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
**RNAV (GPS) PRM Y RWY 8L (SIMULTANEOUS CLOSE  
PARALLEL), ORIG**  
18 SEPTEMBER 2014

SUP:

AMDT: **NONE**

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION****DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KATL
RUNWAY	RW08L
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W08B
LTP/FTP LATITUDE	333858.3235N
LTP/FTP LONGITUDE	0842620.4920W
LTP/FTP ELLIPSOIDAL HEIGHT	+02798
FPAP LATITUDE	333858.3575N
FPAP LONGITUDE	0842433.7600W
THRESHOLD CROSSING HEIGHT (TCH)	00049.9
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0008
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

**CRC REMAINDER**

85F1A34A

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+03093
FPAP ORTHOMETRIC HEIGHT	+03093

QUALITY  
4  
CHECKED

CITY AND STATE

ATLANTA, GA

ELEVATION: 1026

TDZE: 1015

AIRPORT NAME:

HARTSFIELD - JACKSON ATLANTA INTL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
**RNAV (GPS) PRM Y RWY 8L (SIMULTANEOUS CLOSE  
PARALLEL), ORIG**  
18 SEPTEMBER 2014

SUP:

AMDT: **NONE**

DATED: