

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES								MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LNAV: RW08 CLIMB TO 3700 THEN CLIMBING RIGHT TURN TO 8000 DIRECT BACMY AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 035.63 INBOUND. FAS OBST: 1599 AAO 653524N/1445732W 1799 AAO 653724N/1450124W CHART FORT YUKON AWOS-3 CHART CIRCLING ICON							
BACMY		NATSE (FB)		035.63 / 16.09		8000									
NATSE (IAF)		INDEY (FB)		074.43 / 6.00		5900									
INDEY (IF)		FAPEP (FB)		102.12 / 9.40		3000									
FAPEP (FAF)		ZIDAB/4.95 NM TO RW08 (FB)		083.21 / 1.40											
ZIDAB/4.95 NM TO RW08		RW08 (MAP) (FO)		083.21 / 4.95											
RW08 (MAP)		3700 MSL		083.21		3700									
3700 MSL		BACMY (FO)				8000									
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT INDEY 3. FAC: <u>083.21</u> FAF: <u>FAPEP</u> DIST FAF TO MAP: <u>6.35</u> THLD: <u>6.35</u> 4. MIN. ALT: <u>INDEY 5900, FAPEP 3000, ZIDAB/4.95 NM TO RW08 2540</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1</u> IS NOT CLEAR 8. MSA FROM: <u>RW08 6500</u>								MAG VAR: 20E EPOCH YEAR: 2015							
MINIMUMS															
TAKEOFF: <u>SEE FAA FORM 8260-15A FOR THIS AIRPORT</u>						ALTERNATE: N A X									
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	2420	1 1/4	1484	2420	1 1/2	1484		NA			NA				
CIRCLING	2420	1 1/4	1483	2420	1 1/2	1483		NA			NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: USE FORT YUKON ALTIMETER SETTING; WHEN NOT RECEIVED, PROCEDURE NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BACMY ON V301 SOUTHBOUND. CHART NOTE: RWY 08 STRAIGHT-IN AND CIRCLING MINIMUMS NA AT NIGHT. (SEE FORM 8260-10)															
CITY AND STATE CENTRAL, AK				ELEVATION: 937 THRE: 936 AIRPORT NAME: CENTRAL		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMD'T NO./EFFECTIVE DATE: RNAV (GPS) RWY 8, ORIG 29 MAY 2014				SUP: AMDT: NONE DATED			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART PROFILE NOTE: DESCENT ANGLE NA.

CITY AND STATE

CENTRAL, AK

ELEVATION: 937

THRE: 936

AIRPORT NAME:

CENTRAL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 8, ORIG

29 MAY 2014

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

SUP:	
AMDT:	NONE
DATED:	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	BACMY	BACMY	010		IF		FB					
		NATSE	020	IAF	TF		FB	2.0	035.6 (055.6T)	016.1	AA 08000	
	BACMY	INDEY	030		TF		FB	1.0	074.4 (094.4T)	006.0	AA 05900	
		INDEY	010	FACF	IF		FB				AA 05900	
		FAPEP	020	FAF	TF		FB	0.5	102.1 (122.1T)	009.4	AA 03000	
		ZIDAB	021	SDF	TF		FB	0.3	083.2 (103.2T)	001.4	AA 02540	
		RW08	030	MAP	TF		FO	0.3	083.2 (103.2T)	005.0	AT 02420	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		083.2 (103.2T)		AA 03700	
	BACMY	050		DF	R	FO				AA 08000	
	BACMY	060		HM	R	FO		035.6 (055.6T)	007.0	AA 08000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	BACMY	N653225.55	W1460800.37	N6532.426	W14608.006
	FAPEP	N653556.73	W1450214.17	N6535.946	W14502.236
	INDEY	N654056.94	W1452125.74	N6540.949	W14521.429
	NATSE	N654125.34	W1453553.37	N6541.422	W14535.890
	ZIDAB	N653537.49	W1445856.48	N6535.625	W14458.941
	RW08	N653429.14	W1444720.58	N6534.486	W14447.343

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW08	00936	00



CITY AND STATE CENTRAL, AK	ELEVATION: 937	THRE: 936	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 8, ORIG 29 MAY 2014	SUP:
	AIRPORT NAME: CENTRAL				AMDT: NONE
					DATED: