

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM	TO			COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW17 CLIMB TO 4700 THEN CLIMBING LEFT TURN TO 10000 DIRECT FFU VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 340.00 INBOUND. CHART FAS OBST: 4444 TOWER 405107N/1115805W CHART: 4541 TOWER 405328N/1115633W DISTANCE TO THLD FROM 200 HAT: 0.45 NM. CHART VDP AT 1.26 NM TO RW17* *LNAV ONLY. WAAS CHANNEL # 82338 REFERENCE PATH ID: W17A CHART MANDATORY 12000 AT WEBER. LTP HAE: 1269.8 M					
OGD VORTAC (IAF)	UDUZU (TF) (FB) (RNP 1.00)			120.63 / 8.26				11000							
WEBER (IAF)	GORPS (TF) (FB) (RNP 1.00)			152.19 / 5.74				11200							
GORPS	UDUZU (TF) (FB) (RNP 1.00)			152.21 / 6.00				11000							
TUKTE (IAF)	UDUZU (TF) (FB) (RNP 1.00)			168.99 / 10.99				11000							
UDUZU	IVOCY (TF) (FB) (RNP 1.00)			168.99 / 5.17				9000							
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT UDUZU 3. FAC: 168.99 FAF: TIFUL DIST FAF TO MAP: 5.41 THLD: 5.41 4. MIN. ALT: UDUZU 11000, IVOCY 9000, PRYES 7500, TIFUL 6000 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 6000 GS ALT AT: TIFUL 6000 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 55.1 34:1 IS CLEAR 8. MSA FROM: RW17 13000										MAG VAR: 11E EPOCH YEAR: 2020					
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD					
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	4419	2400	200	4419	2400	200	4419	2400	200	4419	2400	200	4419	2400	200
LNAV/VNAV DA	4571	3000	352	4571	3000	352	4571	3000	352	4571	3000	352	4571	3000	352
LNAV MDA	4700	2400	481	4700	2400	481	4700	5000	481	4700	5000	481	4700	5000	481
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -14C (7F) OR ABOVE 49C (121F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON OGD VORTAC AIRWAY RADIALS 068 CW 153. (CONTINUED ON PAGE 2)															
CITY AND STATE			ELEVATION: 4227 TDZE: 4219			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:		
SALT LAKE CITY, UT			AIRPORT NAME:						RNAV (GPS) RWY 17, AMDT 2A				AMDT: 2		
			SALT LAKE CITY INTL						17 AUGUST 2017				DATED 12/10/2015		



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
IVOCY (IF)	PRYES (TF) (FB) (RNP 1.00)	168.99 / 4.72	7500
PRYES	TIFUL (TF) (FB) (RNP 1.00)	168.99 / 4.71	6000
TIFUL (FAF)	RW17 (MAP) (TF) (FO) (RNP 0.30)	168.99 / 5.41	
RW17 (MAP)	4700 MSL (CA)	168.99	4700
4700 MSL	FFU VORTAC (DF) (FO) (RNP 1.00)		10000

NOTES, (CONT.):

CHART NOTE: FOR INOPERATIVE ALS, INCREASE LPV CAT E VISIBILITY TO RVR 4000, LNAV/VNAV CAT E VISIBILITY TO RVR 6000, AND LNAV CAT C/D/E VISIBILITY TO 1 3/8 SM.

CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED.

CHART NOTE: LNAV PROCEDURE NA DURING SIMULTANEOUS OPERATIONS.

CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.

QUALITY
19
CHECKED

CITY AND STATE

SALT LAKE CITY, UT

ELEVATION: 4227

TDZE: 4219

AIRPORT NAME:

SALT LAKE CITY INTL

 FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 17, AMDT 2A

17 AUGUST 2017

SUP:

AMDT: 2

DATED: 12/10/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KSLC
RUNWAY	RW17
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W17A
LTP/FTP LATITUDE	404756.0980N
LTP/FTP LONGITUDE	1115743.4550W
LTP/FTP ELLIPSOIDAL HEIGHT	+12698
FPAP LATITUDE	404621.2940N
FPAP LONGITUDE	1115743.4410W
THRESHOLD CROSSING HEIGHT (TCH)	00055.1
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

42F176A0

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+12868
FPAP ORTHOMETRIC HEIGHT	+12868

QUALITY
19
CHECKED

CITY AND STATE

SALT LAKE CITY, UT

ELEVATION: 4227

TDZE: 4219

AIRPORT NAME:

SALT LAKE CITY INTL

 FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 17, AMDT 2A

17 AUGUST 2017

SUP:

AMDT: 2

DATED: 12/10/2015