

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
NADOE (IAF)	MEKLE (NOPT) (FB)	128.85 / 5.00	2400	LNAV/VNAV: DA LNAV: RW04
LADME (IAF)	MEKLE (NOPT) (FB)	308.93 / 5.00	2400	
MEKLE (IF/IAF)	OHAGU (FB)	038.89 / 6.10	2200	CLIMB TO 2600 DIRECT CERKA AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD NE, RT, 219.08 INBOUND. FAS OBST: 819 AAO 353632N/0952436W 959 AAO 353535N/0952601W. CHART VDP AT 1.35 MILES TO RW04* *LNAV ONLY. CHART APT ELEVATION 611 DISTANCE TO THLD FROM 468 HAT: 1.34 NM

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SW MEKLE, RT, 038.89 INBOUND, 2400 FT. IN LIEU OF PT (IAF)
- FAC: 038.94 FAF: OHAGU DIST FAF TO MAP: 4.80 THLD: 4.80
- MIN. ALT: MEKLE 2400, OHAGU 2200
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 2200 GS ALT AT: OHAGU OM: MM: IM:
- GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR
- MSA FROM:

MAG VAR: 6E

EPOCH YEAR: 1985

MINIMUMS																
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @											
CATEGORY	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV/VNAV DA	1079	1 3/4	468	1079	1 3/4	468	1079	1 3/4	468	1079	1 3/4	468				
LNAV MDA	1080	1	469	1080	1	469	1080	1 1/4	469	1080	1 1/2	469				
CIRCLING	1120	1	509	1160	1	549	1180	1 1/2	569	1200	2	589				

NOTES:
CHART NOTE: STRAIGHT-IN MINIMUMS NA AT NIGHT.
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 47C (116F).
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: BARO-VNAV AND VDP NA WHEN USING TAHEQUAH ALTIMETER SETTING.
SEE 8260-10.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE MUSKOGEE, OK	ELEVATION: 611 TDZE: 611 AIRPORT NAME: DAVIS FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 31 JUL 2008	SUP: AMDT: ORIG DATED 11/28/2002
---------------------------------------	---	-------------------------------------	---	--

QUALITY
CHECKED

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TAHLEQUAH ALTIMETER SETTING AND INCREASE DA 92 FEET AND ALL VISIBILITIES 1/4 MILE, ALL MDA 100 FEET, CAT C AND D VISIBILITIES 1/4 MILE.

TAA

	FROM	TO	ALT
1.	309/30 CW 129/30 (NOPT)	309/10 CW 129/10	3100
2.	309/10 CW 129/10	MEKLE (IF/IAF) (FB)	2400
3.	129/30 CW 219/30	129/10 CW 219/10	3600
4.	129/10 CW 219/10	NADOE (IAF)	2400
5.	219/30 CW 309/30	219/5 CW 309/5	3000
6.	219/5 CW 309/5	LADME (IAF)	2400

CITY AND STATE

MUSKOGEE, OK

ELEVATION: 611 TDZE: 611

AIRPORT NAME:

DAVIS FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 4, AMDT 1

31 JUL 2008

SUP:

AMDT: ORIG

DATED: 11/28/2002

CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	ORIG
DATED:	11/28/2002

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	LADME	LADME	010	IAF	IF		FB				
	LADME	MEKLE	020		TF		FB	1.0	308.9 (315T)	005.0	02400
	MEKLE	MEKLE	010		HF	R	FB		038.9 (045T)	004.0	02400
	NADOE	NADOE	010	IAF	IF		FB				
	NADOE	MEKLE	020		TF		FB	1.0	128.9 (135T)	005.0	02400
		MEKLE	010	FACF	IF		FB				02400
		OHAGU	020	FAF	TF		FB	0.5	038.9 (045T)	006.1	02200
		RW04	030	MAP	TF		FO	0.3	038.9 (045T)	004.8	00651

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	CERKA	040		DF		FO	1.0			02600
	CERKA	050		HM	R	FO	2.0	219.1 (225T)	004.0	02600

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CERKA	N354741.56	W0951208.42	N3547.693	W09512.140
	LADME	N352809.74	W0952723.57	N3528.162	W09527.393
	MEKLE	N353141.87	W0953143.78	N3531.698	W09531.730
	NADOE	N353513.84	W0953604.37	N3535.231	W09536.073
	OHAGU	N353601.59	W0952626.87	N3536.027	W09526.448
	RW04	N353925.55	W0952217.40	N3539.426	W09522.290

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW04	00611	40

CITY AND STATE
MUSKOGEE, OK

ELEVATION: 611 TDZE: 611
 AIRPORT NAME:
 DAVIS FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 4, AMDT 1
 31 JUL 2008

SUP:
 AMDT: ORIG
 DATED: 11/28/2002

CHECKED