

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: HOSUM						
RBRTS (IAF)		CORUB (TF) (FB) (RNP 1.00)		115.27 / 6.49				12700		(DO NOT EXCEED 250 KIAS UNTIL NEBSE) CLIMB TO 13000 DIRECT KUPLE AND ON TRACK 159.79 TO ROCOS AND ON TRACK 114.80 TO PULIE AND ON TRACK 051.40 TO WEBAT AND ON TRACK 341.46 TO TEVOC AND ON TRACK 321.99 TO NEBSE AND ON TRACK 264.38 TO BIH VOR/DME AND HOLD.						
CORUB		HEGIT (TF) (FB) (RNP 1.00)		115.32 / 12.00				9700								
NIKOL (IAF)		FAVEK (TF) (FB) (RNP 1.00)		156.94 / 18.01				12700								
FAVEK		HEGIT (TF) (FB) (RNP 1.00)		156.97 / 6.70				9700								
HEGIT (IF)		MUBOE (TF) (FB) (RNP 1.00)		115.47 / 3.46				8700		ADDITIONAL FLIGHT DATA: HOLD SE, RT, 326.00 INBOUND. FAS OBST: 5619 AAO 372910N/1183155W. CHART: 8959 TERRAIN 371217N/1180625W CHART BISHOP MOA. CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES.						
(SEE FORM 8260-10)																
THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 18-01.																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. PROFILE STARTS AT HEGIT																
3. FAC: 120.40 FAF: JAAKE DIST FAF TO MAP: 8.54 THLD: 9.54																
4. MIN. ALT: HEGIT 9700, MUBOE 8700, JAAKE 7900																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																
8. MSA FROM: HOSUM 15500										MAG VAR: 15E			EPOCH YEAR: 1985			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		@				
CATEGORY ==>		A		B		C		D		E						
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA		6600	1 1/4	2477	6600	1 1/2	2477	6600	3	2477		NA				
CIRCLING		6600	1 1/4	2476	6600	1 1/2	2476	6600	3	2476		NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE AT NEBSE: MAX 250 KIAS CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT NIKOL ON V244-T298 WESTBOUND AND ON V381 NORTHWEST BOUND.																
										@ CAT A, B 2500-2, CAT C 2500-3						
CITY AND STATE BISHOP, CA																
ELEVATION: 4124 TDZE: 4123 AIRPORT NAME: BISHOP				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 12, ORIG-D 1 FEBRUARY 2018				SUP: AMDT: ORIG-C DATED 10/12/2017						



**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<b>FROM</b>	<b>TO</b>	<b>COURSE AND DISTANCE</b>	<b>ALTITUDE</b>
MUBOE	JAAKE (TF) (FB) (RNP 1.00)	115.51 / 2.60	7900
JAAKE (FAF)	HOSUM (MAP) (TF) (FO) (RNP 0.30)	120.40 / 8.54	
HOSUM (MAP)	4524 MSL (CA)	120.40	
4524 MSL	KUPLE (DF) (FB) (RNP 1.00)		4524
KUPLE	ROCOS (TF) (FB) (RNP 1.00)	159.79 / 7.34	
ROCOS	PULIE (TF) (FB) (RNP 1.00)	114.80 / 9.00	
PULIE	WEBAT (TF) (FB) (RNP 1.00)	051.40 / 6.80	
WEBAT	TEVOC (TF) (FB) (RNP 1.00)	341.46 / 5.00	
TEVOC	NEBSE (TF) (FB) (RNP 1.00)	321.99 / 5.20	
NEBSE	BIH VOR/DME (TF) (FO) (RNP 1.00)	264.38 / 13.10	13000

QUALITY  
4  
CHECKED

CITY AND STATE

BISHOP, CA

**ELEVATION: 4124**  
**AIRPORT NAME:**

**TDZE: 4123**  
  
**BISHOP**

**FACILITY IDENTIFIER:**  
**RNAV**

**PROCEDURE NO./AMDT NO./EFFECTIVE DATE:**  
**RNAV (GPS) Y RWY 12, ORIG-D**  
1 FEBRUARY 2018

**SUP:**

**AMDT: ORIG-C**

**DATED: 10/12/2017**