

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		ILS: DA LOC: 5.39 NM AFTER NAPPS INT/I-SBA 6.59 DME OR AT I-SBA 1.21 DME CLIMB TO 700 THEN CLIMBING RIGHT TURN TO 4000 ON RZS VORTAC R-185 TO GOLET INT/RZS 14.43 DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4000. ALTERNATE MA (DO NOT CHART): CLIMB TO 700 THEN CLIMBING RIGHT TURN TO 4000 ON HEADING 160 AND FIM VORTAC (SEE FORM 8260-10) ADDITIONAL FLIGHT DATA: HOLD SE, RT, 307.00 INBOUND. CHART FAS OBST: 239 TREE 342558N/1195422W. CHART VDP AT 2.56 DME* DISTANCE VDP TO THLD 1.35 NM. *LOC ONLY.							
GVO VORTAC (IAF)		YONNI INT/GVO 3.00 DME		163.00 / 3.00				5000									
YONNI INT/GVO 3.00 DME		HABUT INT/I-SBA 12.84 DME		163.00 / 3.53 (GVO R-163) (RZS LR-245)				3500									
GOLET INT/RZS 14.43 DME (IAF)		LOBER INT/FIM 60.11 DME		250.00 / 11.05 (FIM R-250)				4000									
LOBER INT/FIM 60.11 DME		HABUT INT/I-SBA 12.84 DME		343.00 / 9.53 (GVO R-163) (RZS LR-231)				3500									
HABUT INT/I-SBA 12.84 DME (IF)		GOYED INT/I-SBA 9.48 DME		074.55 / 3.36 (I-SBA)				2700									
GOYED INT/I-SBA 9.48 DME		NAPPS INT/I-SBA 6.59 DME		074.55 / 2.89 (I-SBA)				1800									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																	
2. PROFILE STARTS AT HABUT																	
3. FAC: 074.55 FAF: NAPPS INT/I-SBA 6.59 DME DIST FAF TO MAP: 5.39 THLD: 5.39																	
4. MIN. ALT: HABUT 3500, GOYED 2700, NAPPS 1800																	
5. DIST TO THLD FROM OM: - MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: 1000																	
6. MIN GS INCPT: 1800 GS ALT AT: NAPPS 1800 OM: - MM: - IM: -																	
7. GS ANGLE: 3.00 TCH: 48.1																	
8. MSA FROM: RZS VORTAC 030-120 8800, 120-210 5200, 210-300 5800, 300-030 8100																	
MAG VAR: 14E EPOCH YEAR: 1985																	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		ILS: #		LOC: STANDARD @			
CATEGORY ==>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
S-ILS 07**	213	2400	200	213	2400	200	213	2400	200	213	2400	200					
S-LOC 07	500	2400	487	500	2400	487	500	4000	487	500	5000	487					
CIRCLING	800	1	787	800	1 1/4	787	800	2 1/4	787	1000	3	987					
NOTES: CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA (NA WHEN USING OXNARD ALTIMETER SETTING). CHART NOTE: CIRCLING RWY 15R NA AT NIGHT. CHART NOTE: VDP NA WHEN USING OXNARD ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OXNARD ALTIMETER SETTING AND INCREASE ALL (CONTINUED ON PAGE 2)																	
CITY AND STATE SANTA BARBARA, CA		ELEVATION: 13 TDZE: 13 AIRPORT NAME: SANTA BARBARA MUNI		FACILITY IDENTIFIER: I-SBA		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 7, AMDT 5B 1 FEBRUARY 2018						SUP: AMDT: 5A DATED 04/28/2016					

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.
CAT A, B 800-2, CAT C 800-2 1/4, CAT D 1000-3
@ CAT C 800-2 1/4, CAT D 1000-3

QUALITY
5
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

MISSED APPROACH INSTRUCTIONS, (CONT.):

R-250 TO GOLET INT/FIM 49.06 DME AND HOLD E, RT, 250.00 INBOUND.

NOTES, (CONT.):

DA/MDA 100 FT, AND S-LOC CAT C VISIBILITY TO RVR 5000, CAT D VISIBILITY TO RVR 6000. INCREASE

CIRCLING CAT A VISIBILITY 1/4 MILE, CAT C VISIBILITY 1/2 MILE.

FOR INOPERATIVE ALS WHEN USING OXNARD ALTIMETER SETTING, INCREASE S-ILS 7 ALL CATS VISIBILITY TO RVR 5000.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT GVO VORTAC ON T261 NORTHWEST BOUND.

QUALITY
5
CHECKED

CITY AND STATE

SANTA BARBARA, CA

ELEVATION: 13

TDZE: 13

AIRPORT NAME:

SANTA BARBARA MUNI

FACILITY
IDENTIFIER:
I-SBA

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

ILS OR LOC RWY 7, AMDT 5B

1 FEBRUARY 2018

SUP:

AMDT: **5A**

DATED: **04/28/2016**