

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		RNP: DA CLIMB TO 3000 ON TRACK 123.19 TO ODITY AND ON TRACK 071.17 TO TOY VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, RT, 083.00 INBOUND. ROUTE TYPE: A, H ROUTE TYPE QUALIFIER 1: F ROUTE TYPE QUALIFIER 2: S DISTANCE TO THLD FROM 502 HAT: 1.45 NM. CHART AT OR ABOVE 5000 AT HRBEE AND RRIIP CHART AT OR ABOVE 8000, AT OR BELOW 9000 AT VEEGE CHART MANDATORY 7000 AT STAAN CHART AT OR ABOVE 6000 AT RUYON #TCH 581.9 (DO NOT CHART) CHART PLANVIEW NOTE: RADAR REQUIRED					
STAAN (IAF)		KARRP (TF) (FB) (RNP 1.00)		083.65 / 5.53				6000							
KARRP		AARBY (TF) (FB) (RNP 1.00)		083.70 / 4.21				4000							
AARBY (IF)		FARIS (TF) (FB) (RNP 1.00)		083.75 / 6.91				3400							
RUYON (IAF)		EUBIE (TF) (FB) (RNP 1.00)		122.98 / 5.64				4200							
EUBIE (IF)		FARIS (TF) (FB) (RNP 1.00)		123.04 / 4.43				3400							
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)														MAG VAR: 1W EPOCH YEAR: 2020	
2. PROFILE STARTS AT KIRKA															
3. FAC: <u>123.15</u> FAF: _____ DIST FAF TO MAP: _____ THLD: _____															
4. MIN. ALT: KIRKA 2400, OHROB 1700															
5. DIST TO THLD FROM OM: <u>3.51</u> MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: <u>1700</u> GS ALT AT: OHROB 1700 OM: _____ MM: _____ IM: _____															
7. GS ANGLE: <u>3.00</u> TCH: <u>53.6</u> # <u>20:1 IS CLEAR</u> <u>34:1 IS NOT CLEAR</u>															
8. MSA FROM: RW12L 3000															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD					
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
AUTHORIZATION REQUIRED															
RNP 0.30 DA	1043	6000	502	1043	6000	502	1043	6000	502	1043	6000	502			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: GPS REQUIRED. CHART SPEED ICON IN PLANVIEW AT RUYON : MAX 250 KIAS. CHART SPEED ICON IN PLANVIEW AT STAAN : MAX 250 KIAS. (CONTINUED ON PAGE 2)															
CITY AND STATE		ELEVATION: 618		TDZE: 541		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
ST LOUIS, MO		AIRPORT NAME:		ST LOUIS LAMBERT INTL				RNAV (RNP) Z RWY 12L, ORIG-C				AMDT: ORIG-B			
								29 MARCH 2018				DATED 08/17/2017			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33				
TERMINAL ROUTES, (CONT.):				
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
VEEGE (IAF)	YADDI (TF) (FB) (RNP 1.00)	148.06 / 10.27	5500	
YADDI	CORDL (TF) (FB) (RNP 1.00)	148.13 / 5.70	4000	
CORDL (IF)	FARIS (TF) (FB) (RNP 1.00)	148.13 / 6.23	3400	
RRIPP (IF)	SSAMM (TF) (FB) (RNP 1.00)	302.80 / 2.91	5000	
SSAMM	KIRKA (RF) (FB) (RNP 1.00)	(2.61 NM RADIUS CW (CFBPX))/8.21	2400	
FARIS	KIRKA (TF) (FB) (RNP 1.00)	123.07 / 2.84	2400	
HRBEE (IF)	BUFEE (TF) (FB) (RNP 1.00)	301.32 / 2.89	5000	
BUFEE	KIRKA (RF) (FB) (RNP 1.00)	(2.80 NM RADIUS CCW (CFBPV))/8.71	2400	
KIRKA	OHROB (TF) (FB) (RNP 1.00)	123.14 / 2.58	1700	
OHROB (FAF)	RW12L (MAP) (TF) (FO) (RNP 0.30)	123.15 / 3.51		
RW12L (MAP)	ODITY (TF) (FB)	123.19 / 9.92		
ODITY	TOY VORTAC (TF) (FO)	071.17 / 13.43	3000	
NOTES, (CONT.): CHART SPEED ICON IN PLANVIEW AT AARBY : MAX 250 KIAS. CHART SPEED ICON IN PLANVIEW AT KARRP : MAX 250 KIAS. CHART SPEED ICON IN PLANVIEW AT EUBIE : MAX 250 KIAS. CHART SPEED ICON IN PLANVIEW AT VEEGE : MAX 250 KIAS. CHART SPEED ICON IN PLANVIEW AT RRIPP : MAX 250 KIAS. CHART SPEED ICON IN PLANVIEW AT CORDL : MAX 250 KIAS. CHART SPEED ICON IN PLANVIEW AT FARIS : MAX 250 KIAS. CHART SPEED ICON IN PLANVIEW AT SSAMM : MAX 210 KIAS. CHART SPEED ICON IN PLANVIEW AT HRBEE : MAX 250 KIAS. CHART SPEED ICON IN PLANVIEW AT BUFEE : MAX 210 KIAS. CHART SPEED ICON IN PLANVIEW AT KIRKA : MAX 210 KIAS. CHART SPEED ICON IN PLANVIEW AT OHROB : MAX 165 KIAS.				
CITY AND STATE	ELEVATION: 618	TDZE: 541	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
ST LOUIS, MO	AIRPORT NAME:		RNAV	RNAV (RNP) Z RWY 12L, ORIG-C
	ST LOUIS LAMBERT INTL			29 MARCH 2018
			SUP:	
			AMDT:	ORIG-B
			DATED:	08/17/2017



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
**RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CHART PLANVIEW NOTE ADJACENT TO RRIPP IF: RF REQUIRED.

CHART PLANVIEW NOTE ADJACENT TO HRBEE IF: RF REQUIRED.

CHART NOTE: FOR INOPERATIVE ALS, INCREASE RNP 0.30 ALL CATS VISIBILITY TO 1 3/4 SM.

CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 11, EXCEPT FOR ARRIVALS AT RRIPP AND HRBEE.

CHART NOTE: USE OF FD OR AP REQUIRED DURING SIMULTANEOUS OPERATIONS.

CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS.

QUALITY
26
CHECKED

CITY AND STATE

ST LOUIS, MO

ELEVATION: 618

TDZE: 541

AIRPORT NAME:

ST LOUIS LAMBERT INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (RNP) Z RWY 12L, ORIG-C

29 MARCH 2018

SUP:

AMDT: **ORIG-B**

DATED: **08/17/2017**