

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
WENDA (IAF)	JETOR (NOPT) (FB)	012.50 / 5.00	2700	LNAV: RW28	
HIMAR (IAF)	JETOR (NOPT) (FB)	192.50 / 5.00	2700		
JETOR (IF/IAF)	JINET (FB)	282.50 / 6.10	1800	CLIMB TO 2700 DIRECT FOLAM AND HOLD.	
				ADDITIONAL FLIGHT DATA: HOLD W, RT, 102.17 INBOUND. CHART FAS OBS: 605 TOWER 402336N/0743506W CHART A-220. JINET TO RW28: 3.04/42 CHART TRENTON MERCER ASOS, 133.7.	

- PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- HOLD E JETOR, RT, 282.50 INBOUND, 2700 FT. IN LIEU OF PT (IAF)
- FAC: 282.41 FAF: JINET DIST FAF TO MAP: 5.05 THLD: 5.05
- MIN. ALT: JETOR 2700, JINET 1800
- DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
- MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____
- GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR
- MSA FROM: _____

MAG VAR: 13W EPOCH YEAR: 2005

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A	X					
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	900	1	772	900	1 1/4	772	900	2 1/4	772		NA				
CIRCLING	900	1	772	900	1 1/4	772	900	2 1/4	772		NA				

NOTES:
 CHART NOTE: USE TRENTON MERCER ALTIMETER SETTING, IF NOT RECEIVED USE SOMERSET ALTIMETER SETTING.
 CHART NOTE: PROCEDURE NA AT NIGHT.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CITY AND STATE PRINCETON/ROCKY HILL, NJ	ELEVATION: 128 TDZE: 128	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 28, ORIG NOV 23 2006	SUP:
	AIRPORT NAME: PRINCETON			AMDT: NONE
				DATED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	193/30 CW 013/30 (NOPT)	JETOR (IF/IAF) (FB)	2700
2.	013/30 CW 103/30	WENDA (IAF) (FB)	2700
3.	103/30 CW 193/30	HIMAR (IAF) (FB)	2800

CITY AND STATE

PRINCETON/ROCKY HILL, NJ

ELEVATION: 128 TDZE: 128

AIRPORT NAME:

PRINCETON

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 28, ORIG

NOV 23 2006

SUP:

AMDT: NONE

DATED: