

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE				ALTITUDE		MAP: MAJOJ/MFD 11.70 DME FIX							
MFD VORTAC (IF/IAF)			YUMAN/MFD VORTAC 7.50 DME			332.28 / 7.50				3000		CLIMB TO 3000 THEN RIGHT TURN DIRECT MFD VORTAC AND HOLD.							
THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 18-09.										ADDITIONAL FLIGHT DATA: HOLD SE, LT, 332.00 INBOUND. FAS OBST: 1299 AAO 405757N/0824104W. CHART CIRCLING ICON. FAC CROSSES MIDPOINT OF RWY 10-28.									
1. PT <u>R</u> SIDE OF COURSE <u>152.28</u> OUTBOUND <u>3000</u> FT WITHIN <u>10</u> MILES OF <u>MFD VORTAC</u> (IAF)																			
2.																			
3. FAC <u>332.28</u> FAF <u>YUMAN/MFD VORTAC 7.50 DME</u> DIST FAF TO MAP <u></u> THLD <u></u>																			
4. MIN. ALT <u>MFD VORTAC 3000, YUMAN 3000</u>																			
8. MSA FROM: <u>MFD VORTAC 3000</u>										MAG VAR: <u>3W</u> EPOCH YEAR: <u>1965</u>									
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X									
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
CIRCLING		1680	1	713	1720	1	753	1880	2 3/4	913		NA							
CLEVELAND-HOPKINS ALTIMETER SETTING MINIMUMS																			
CIRCLING		1720	1	753	1760	1	793	1920	3	953		NA							
NOTES:																			
CHART NOTE: USE MANSFIELD ALTIMETER SETTING, WHEN NOT RECEIVED, USE CLEVELAND-HOPKINS ALTIMETER SETTING.																			
EQUIPMENT REQUIREMENTS NOTE: RADAR REQUIRED FOR PROCEDURE ENTRY, DME REQUIRED.																			
CITY AND STATE		ELEVATION: 967			TDZE:			FACILITY IDENTIFIER:			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP				
WILLARD, OH		AIRPORT NAME:						MFD			VOR-A, ORIG-B 24 MAY 2018				AMDT ORIG-A				
		WILLARD													DATE 10/12/2017				

