

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>VOR STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23</b>								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 5.47 MILES AFTER RITRO INT/15.00 DME OR AT MADDA/ 20.47 DME FIX  CLIMBING LEFT TURN TO 2500 ON FBC VORTAC R-104 TO RITRO INT/15.00 DME AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD W, RT, 104.00 INBOUND. CHART FAS OBST: 995 TOWER 405302N/0832012W CHART 1324 TOWER 405559N/0832248W. FAC CROSSES MID POINT OF RWY 18-36.						
FBC VORTAC (IF/IAF)		RITRO INT/ 15.00 DME		104.00 / 15.00				2500								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W FBC VORTAC, RT, 104.00 INBOUND, 2500 FT. IN LIEU OF PT (IAF) 3. FAC 104.00 FAF RITRO INT/ 15.00 DME _____ DIST FAF TO MAP 5.47 THLD _____ 4. MIN. ALT FBC VORTAC 2500, RITRO 2500, YEVUN/FBC 18.00 DME 1520 8. MSA FROM: FBC VORTAC 3000										MAG VAR: 2W		EPOCH YEAR: 1965				
<b>MINIMUMS</b>																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		<input checked="" type="checkbox"/> X						
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
CIRCLING	1520	1	690	1520	1 1/4	690	1520	2	690	1520	2 1/4	690				
<b>YEVUN FIX MINIMUMS (DME REQUIRED)</b>																
CIRCLING	1340	1	510	1340	1 1/4	510	1340	1 1/2	510	1380	2	550				
NOTES: CHART NOTE: PROCEDURE NA AT NIGHT. CHART PLANVIEW NOTE: ADF OR DME REQUIRED. CHART NOTE: USE FINDLAY ALTIMETER SETTING, WHEN NOT RECEIVED, USE MARION ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET. CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON FBC VORTAC AIRWAY RADIALS 200 CW 012.																
CITY AND STATE		ELEVATION: 830		TDZE:		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP VOR OR GPS-A				
UPPER SANDUSKY, OH		AIRPORT NAME:		WYANDOT COUNTY		FBC		VOR-A, AMDT 3C 15 NOVEMBER 2012				AMDT 3B				
												DATE 07/01/2010				