

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
YOSEMITE	THREE	YOSE3.NTELL	TWO	12/07/2017	ROUTINE
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

19JULY2018

DP ROUTE DESCRIPTION:

TAKEOFF RWY 11L/R: CLIMB HEADING 112.35, THENCE...

TAKEOFF RWY 29L: CLIMB HEADING 292.36, THENCE...

TAKEOFF RWY 29R: CLIMB HEADING 292.37, THENCE...

...MAINTAIN ATC ASSIGNED ALTITUDE; EXPECT CLEARANCE TO FILED ALTITUDE FIVE MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PROCEDURAL DATA NOTES:

NOTE: RADAR REQUIRED

TAKEOFF MINIMUMS:

RWY 11L/R: STANDARD

RWY 29L/R: STANDARD

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:**LOST COMMUNICATIONS PROCEDURES:**

IF NOT IN CONTACT WITH FRESNO DEPARTURE CONTROL WITHIN TWO MINUTES OF TAKEOFF, AIRCRAFT ENROUTE TO FRA, MVA, FMG AND OAL PROCEED DIRECT FRA VORTAC, CROSS FRA VORTAC AT OR ABOVE 9000 FT, THENCE VIA ASSIGNED ROUTE TO FILED ALTITUDE.

ADDITIONAL FLIGHT DATA:

CHART: TOP ALTITUDE: ASSIGNED BY ATC.

REFERENCE MAG VAR: KFAT 13E EPOCH YR:2020.

QUALITY
3
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
YOSEMITE	THREE	YOSE3.NTELL	TWO	12/07/2017	ROUTINE

19JULY2018

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
FRESNO YOSEMITE INTL (KFAT)	FRESNO	CA

COMMUNICATIONS:

ATIS, CLNC DEL, GND CON, FRESNO DEP CON 119.6, FRESNO TWR.

FIXES AND/OR NAVAIDS:

FMG VORTAC, MVA VORTAC, OAL VORTAC, FRA VORTAC, PXN VORTAC.

REMARKS:

ABBREVIATED AMENDMENT.

FLIGHT INSPECTED BY:

Digitally signed by

ROBERT G HAMILTON

Apr 17, 2018

JEFFREY ECKMAN

OFFICE SYMBOL:

FICO

DATE:

4/16/18

DEVELOPED BY:

Digitally signed by

JOHN HAZELTON

Feb 22, 2018

JOHN HAZELTON

OFFICE SYMBOL:

AJV-5421

DATE:

02/22/2018

APPROVED BY:

Digitally signed by

ROBERT G HAMILTON

Apr 17, 2018

JULIE MORGAN

OFFICE SYMBOL:

AJV-5420

DATE:

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

<u>A4A</u>	<u>ALPA</u>	<u>AOPA</u>	<u>APA</u>	<u>HAI</u>	<u>NBAA</u>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

OTHER:

ATA, ZOA, FRESNO ATCT, FRESNO APP CON, ARPT MGR, WST FPO.

CHANGES - REASONS:

1. UPDATED TAKEOFF RWY 29L/R: FROM CLIMB HEADING 292.36, THENCE...TO TAKEOFF RWY 29L: CLIMB HEADING 292.36, THENCE...AND TAKEOFF RWY 29R: CLIMB HEADING 292.37, THENCE...
2. DELETED TO 2000, THEN CONTINUE CLIMB FOR RADAR VECTORS TO JOIN ASSIGNED ROUTE FROM BOTH 11L/R AND 29 L/R DP ROUTE DESCRIPTIONS PER IAP CHECKLIST AND ATC REQUEST.
3. DELETED HYP VOR/DME FROM FIXES AND/OR NAVAIDS-RE: PER IAP CHECKLIST AND ATC REQUEST.

QUALITY
3
CHECKED