

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES										MISSED APPROACH										
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: WAPIG/YJN 20.95 DME									
BTV VOR/DME			GOOTH/YJN 16.00 DME			017.07 / 37.28			2900		CLIMBING RIGHT TURN TO 1800 ON YJN VOR/DME R-169 TO GOOTH/YJN 16.00 DME AND HOLD.									
YJN VOR/DME (IAF)			FOBOP/YJN 8.00 DME (NOPT)			169.06 / 8.00			1800											
FOBOP/YJN 8.00 DME (IF)			GOOTH/YJN 16.00 DME			169.06 / 8.00 (YJN R-169)			1800											
THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 18-13.										ADDITIONAL FLIGHT DATA: FAS OBST: 612 AAO 445803N/0730414W. GOOTH TO RW19: 2.91/45										
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																				
2. HOLD N GOOTH, RT, 169.06 INBOUND, 1800 FT. IN LIEU OF PT (IAF)																				
3. FAC 169.06 FAF GOOTH/YJN 16.00 DME										DIST FAF TO MAP _____ THLD 4.95										
4. MIN. ALT GOOTH 1800																				
8. MSA FROM: YJN VOR/DME 145-015 2600, 015-145 3600										MAG VAR: 16W EPOCH YEAR: 1985										
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X										
CATEGORY =====>		A			B			C			D			E						
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA					
S-19	880	1	652	880	1	652		NA			NA									
CIRCLING	880	1	652	880	1 1/4	652		NA			NA									
NOTES:																				
CHART NOTE: RWY 19 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.																				
CHART NOTE: PROCEDURE NA AT NIGHT.																				
CHART EQUIPMENT REQUIREMENTS NOTE: DME REQUIRED FOR PROCEDURE ENTRY																				
CHART EQUIPMENT REQUIREMENTS NOTE: DME REQUIRED																				
(CONTINUED ON PAGE 2)																				
CITY AND STATE HIGHGATE, VT				ELEVATION: 228 TDZE: 228 AIRPORT NAME: FRANKLIN COUNTY STATE				FACILITY IDENTIFIER: YJN		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 19, AMDT 5B 19 JULY 2018						SUP VOR/DME RWY 19				
																AMDT 5A				
																DATE 12/11/2014				

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PLATTSBURGH ALTIMETER SETTING AND INCREASE ALL MDA 60 FT.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON YJN VOR/DME AIRWAY RADIAL 175.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON BTV VOR/DME AIRWAY RADIAL 014.

QUALITY
11
CHECKED

CITY AND STATE

HIGHGATE, VT

ELEVATION: 228**TDZE: 228**

AIRPORT NAME:

FRANKLIN COUNTY STATE

FACILITY
IDENTIFIER:

YJN

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 19, AMDT 5B

19 JULY 2018

SUP: **VOR/DME RWY 19**AMDT: **5A**DATED: **12/11/2014**