

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> HALF MOON BAY	<u>AIRPORT ID</u> KHAF	<u>PROCEDURE NAME</u> RNAV (GPS) Z RWY 12	<u>ORIGINAL/AMENDMENT</u> ORIG-B	<u>CITY</u> HALF MOON BAY	<u>STATE</u> CA
<u>AIRPORT ELEVATION</u> 66	<u>TDZE</u> 59	<u>SUPERSEDED</u> RNAV (GPS) Z RWY 12	<u>ORIGINAL/AMENDMENT</u> ORIG-A	<u>DATED</u> 02/09/2012	<u>MAG VAR</u>
<u>FACILITY</u>	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u>	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u> CANCEL	

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE

PROCEDURE CANCELLED EFFECTIVE 28 FEBRUARY 2019

MISSED APPROACH

MAP:

MISSED APPROACH INSTRUCTIONS:

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF (IAF)
2.				
3. FAC:	PFAF:	DIST PFAF TO MAP:		DIST PFAF TO THLD:
4. MIN ALT:				
5. DIST TO THLD FROM OM:	MM:	IM:	150 HAT:	336 HAT: GS ANT:
6. MIN GP INCPT:	GP ALT AT PFAF :		OM:	MM: IM:
7. GP ANGLE:	34:1:	20:1:	TCH:	
8. MSA FROM:				

PBN REQUIREMENTS NOTE:



ADDITIONAL FLIGHT DATA:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

11

[illegible]

CHANGES - REASONS

COORDINATED WITH:

A4A ☐ **ALPA** ☐ **AOPA** ☐ **APA** ☐ **HAI** ☐ **NBAA** ☐ **OTHER:** NORCAL, ZOA, AIRPORT MANAGER

FLIGHT CHECKED BY

OFFICE

DATE

DEVELOPED BY
DAVID DANNER (JOSEPH HILLEY)

Digitally signed by
ROBERT G HAMILTON
Dec 10, 2018

OFFICE
AJV-5421

DATE
10/09/2018

APPROVED BY
JULIE A. MORGAN

Digitally signed by
ROBERT G HAMILTON
Dec 10, 2018

OFFICE
AJV-5420

DATE

TITLE

