

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE		ALTITUDE		RNP: DA									
CVO VOR/DME (IAF)		HOCUM (TF) (FB) (RNP 1.00)		134.00 / 5.87		3000		CLIMB TO 5000 DIRECT TIPIE, AND ON TRACK 209.38 TO ROKBE, AND TRACK 254.32 TO VAUGN AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5000.									
SHEDD (IAF)		HOCUM (TF) (FB) (RNP 1.00)		223.23 / 6.84		3000											
SAGIN (IAF)		HIDJI (TF) (FB) (RNP 1.00)		320.99 / 16.81		3900											
VAUGN (IAF)		HIDJI (TF) (FB) (RNP 1.00)		013.47 / 10.81		3900											
VIDAS (IAF)		YOYUT (TF) (FB) (RNP 1.00)		264.98 / 15.41		5000											
(SEE FORM 8260-10)								ADDITIONAL FLIGHT DATA: HOLD SW, LT, 029.50 INBOUND. ROUTE TYPE QUALIFIER 2: S ROUTE TYPE: A, R ROUTE TYPE QUALIFIER 1: F DISTANCE TO THLD FROM 250 HAT: 0.64 NM. # TCH 411.4 MSL (DO NOT CHART)									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																	
2. PROFILE STARTS AT FIDOL																	
3. FAC: 164.38 FAF: _____ DIST FAF TO MAP: _____ THLD: _____																	
4. MIN. ALT: FIDOL 1400																	
5. DIST TO THLD FROM OM: 3.10 MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																	
6. MIN GS INCPT: 1400 GS ALT AT: FIDOL 1400 OM: _____ MM: _____ IM: _____																	
7. GS ANGLE: 3.00 TCH: 51.2 # 20:1 IS CLEAR 34:1 IS CLEAR																	
8. MSA FROM: RW16R 5300										MAG VAR: 15E				EPOCH YEAR: 2020			
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD					
CATEGORY ==>>>		A		B		C		D		E							
		DH/MDA VIS HAT/HAA		DH/MDA VIS HAT/HAA		DH/MDA VIS HAT/HAA		DH/MDA VIS HAT/HAA		DH/MDA VIS HAT/HAA		DH/MDA VIS HAT/HAA		DH/MDA VIS HAT/HAA		DH/MDA VIS HAT/HAA	
AUTHORIZATION REQUIRED																	
RNP 0.17 DA		614 2400 250		614 2400 250		614 2400 250		614 2400 250		614 2400 250							
RNP 0.30 DA		711 3000 347		711 3000 347		711 3000 347		711 3000 347		711 3000 347							
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -9C OR ABOVE 54C. CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED. CHART SPEED ICON IN PLANVIEW AT ZARSO : MAX 180 KIAS. CHART SPEED ICON IN PLANVIEW AT OVOJO : MAX 180 KIAS. (CONTINUED ON PAGE 2)																	
CITY AND STATE EUGENE, OR		ELEVATION: 374 TDZE: 364 AIRPORT NAME: MAHLON SWEET FIELD				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 16R, AMDT 1B, 10/11/2018						SUP: AMDT: 1A DATED 02/01/2018			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33				
TERMINAL ROUTES, (CONT.):				
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
YOYUT	HIVAM (TF) (FB) (RNP 1.00)	264.74 / 2.01	4700	
HIVAM	FITOK (TF) (FB) (RNP 1.00)	264.71 / 2.61	3400	
HOCUM (IF)	FIDOL (TF) (FB) (RNP 1.00)	164.38 / 13.71	1400	
HIDJI (IF)	ZARSO (TF) (FB) (RNP 1.00)	344.39 / 4.43	3300	
ZARSO	WASEK (RF) (FB) (RNP 1.00)	(2.40 NM RADIUS CW (CFVKD))/3.13	2500	
WASEK	WODGO (RF) (FB) (RNP 1.00)	(2.40 NM RADIUS CW (CFVKD))/2.00	2000	
WODGO	FIDOL (RF) (FB) (RNP 1.00)	(2.40 NM RADIUS CW (CFVKD))/2.40	1400	
FITOK (IF)	OVOJO (TF) (FB) (RNP 1.00)	264.66 / 2.21	2700	
OVOJO	FIDOL (RF) (FB) (RNP 1.00)	(2.40 NM RADIUS CCW (CFPKQ))/4.20	1400	
FIDOL (FAF)	RW16R (MAP) (TF) (FO) (RNP 0.30)	164.38 / 3.10		
RW16R (MAP)	614 MSL (CA)	164.38		
614 MSL	TIPIE (DF) (FB) (RNP 1.00)			
TIPIE	ROKBE (TF) (FB) (RNP 1.00)	209.38 / 6.72		
ROKBE	VAUGN (TF) (FO) (RNP 1.00)	254.32 / 5.34	5000	
NOTES, (CONT.): CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SAGIN ON V23 SOUTHBOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT VAUGN ON V495 SOUTHBOUND AND V121 SOUTHWEST BOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT VIDAS ON V121 EASTBOUND.				
CITY AND STATE EUGENE, OR	ELEVATION: 374 AIRPORT NAME: MAHLON SWEET FIELD	TDZE: 364	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 16R, AMDT 1B, 10/11/2018
			SUP:	
			AMDT:	1A
			DATED:	02/01/2018

QUALITY  
42  
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV (RNP) - STANDARD,  
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON CVO VOR/DME AIRWAY RADIALS 081 CW 217.  
CHART PLANVIEW NOTE ADJACENT TO SAGIN IAF: RF REQUIRED.  
CHART PLANVIEW NOTE ADJACENT TO VAUGHN IAF: RF REQUIRED.  
CHART PLANVIEW NOTE ADJACENT TO VIDAS IAF: RF REQUIRED.  
CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS.  
PBN REQUIREMENTS NOTE: RNP AR APCH.  
CHART NOTE: FOR INOPERATIVE ALS, INCREASE RNP 0.17 ALL CATS VISIBILITY TO RVR 4000 AND RNP 0.30 ALL CATS VISIBILITY TO RVR 5500.

QUALITY  
42  
CHECKED

CITY AND STATE  
EUGENE, OR

ELEVATION: 374 TDZE: 364  
AIRPORT NAME:  
MAHLON SWEET FIELD

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (RNP) Z RWY 16R, AMDT 1B, 10/11/2018

SUP:  
AMDT: 1A  
DATED: 02/01/2018