

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>CITY, STATE</u>	<u>AIRPORT</u>	<u>EFFECTIVE DATE</u>	<u>AMDT NO</u>
SALEM, OH	SALEM AIRPARK INC	24 MAY 2018	2

TAKEOFF MINIMUMS:

RWY 10R, 28L: NA - ENVIRONMENTAL.

RWY 28R: STANDARD.

RWY 10L: STANDARD WITH MINIMUM CLIMB OF 217 FT PER NM TO 1800, OR 1400-3 FOR VCOA.

TEXTUAL DEPARTURE PROCEDURES:

RWY 28R: CLIMB ON HEADING 277.08 TO 2200 BEFORE TURNING LEFT.

VISUAL CLIMB OVER AIRPORT:

RWY 10L - OBTAIN ATC APPROVAL FOR VCOA WHEN REQUESTING IFR CLEARANCE. CLIMB IN VISUAL CONDITIONS TO CROSS SALEM AIRPARK INC AT OR ABOVE 2400 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 10L: TOWER, 3186 FT FROM DER, 654 FT LEFT OF CENTERLINE, 72 FT AGL/1305 FT MSL.

CONTROLLING OBSTACLES:

RWY 10L: 1607 TOWER 405653.00N/0804743.00W (CG/CGTA)

RWY 10L: (VCOA) 2040 FEET MSL TOWER 405423.00N/0805439.00W

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: **RWY 28R:** 2040 FEET MSL TOWER 405423.00N/0805439.00W

REMARKS:

FLIGHT INSPECTED BY:

GLEN B FREEMAN

Digitally signed by

DION E LANCIA

Mar 02, 2018

OFFICE SYMBOL:

FICO

DATE:

02/27/2018

DEVELOPED BY:

VICTOR NASO
(DAVID FRESELLA)

Digitally signed by

DION E LANCIA

Mar 02, 2018

OFFICE SYMBOL:

AJV-5413

DATE:

01/16/2017

APPROVED BY:

GEORGE DAVIS

Digitally signed by

DION E LANCIA

Mar 02, 2018

OFFICE SYMBOL:

AJV-5410

DATE:

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A **ALPA** **AOPA** **APA** **HAI** **NBAA**



OTHER:

ZOB, CAK ATCT, AMGR

CHANGES - REASONS:

1. CHANGED RWY 10/28 TO RWY 10L/28R.
2. ADDED RWY 10R, 28L: NA - ENVIRONMENTAL.
3. CHANGED RWY 10L TAKEOFF MINIMUMS FROM STANDARD TO STANDARD WITH MINIMUM CLIMB OF 217 FT PER NM TO 1800, OR 1400-3 FOR VCOA.
4. DELETED RWY 10L TEXTUAL DEPARTURE PROCEDURE.
4. UPDATED RWY 28R TEXTUAL DEPARTURE PROCEDURE TO CURRENT CRITERIA VERBIAGE.
6. ADDED VCOA FOR RWY 10L.
7. ADDED RWY 10L TAKEOFF OBSTACLE NOTES.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>CITY, STATE</u>	<u>AIRPORT</u>	<u>EFFECTIVE DATE</u>	<u>AMDT NO</u>
SALEM, OH	SALEM AIRPARK INC	24 MAY 2018	2

REASONS:

1. 2. RWY 10R/28L (TURF) ADDED TO AIRPORT.
3. 4. 5. 6. 7. NEW BIENNIAL REVIEW OBSTACLE EVALUATION USING TARGETS.

