

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM	TO			COURSE AND DISTANCE			ALTITUDE		LNAV: RW09 CLIMBING LEFT TURN TO 2000 DIRECT JOSEM AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 179 TOWER 391305N/0753821W CHART 201 TREE 391155N/0753921W CHART CIRCLING ICON. URESY TO RW9: 3.00/40. CHART DOVER AFB ATIS FREQUENCY.						
BLARE	JOSEM (TF) (FO) (RNP 2.00)			231.82 / 19.04			2000								
ENO VORTAC	JOSEM (TF) (FO) (RNP 2.00)			266.91 / 14.41			2000								
GOLDA (IAF)	JOSEM (NOPT) (TF) (FB) (RNP 1.00)			103.06 / 10.89			2000								
PRICE (IAF)	JOSEM (NOPT) (TF) (FB) (RNP 1.00)			031.86 / 4.98			2000								
JOSEM (IF/IAF) (SEE FORM 8260-10)	URESY (TF) (FB) (RNP 1.00)			085.19 / 5.00			1700								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W JOSEM, RT, 085.19 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: 085.26 FAF: URESY DIST FAF TO MAP: 5.06 THLD: 5.06 4. MIN. ALT: JOSEM 2000, URESY 1700, YEHJU/2.50 NM TO RW09 880 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW09 1700										MAG VAR: 12W		EPOCH YEAR: 1995			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A <input checked="" type="checkbox"/> X								
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	460	1	405	460	1	405	460	1 1/8	405	460	1 1/8	405			
CIRCLING	520	1	465	820	1	765	820	2 1/4	765	820	2 1/2	765			
NOTES: CHART NOTE: RWY 9 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GOLDA ON V312 SOUTHWEST BOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON ENO VORTAC AIRWAY RADIALS 189 CW 226. CHART NOTE: USE DOVER AFB ALTIMETER SETTING.															
CITY AND STATE			ELEVATION: 55 TDZE: 55			FACILITY IDENTIFIER:			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:		
DOVER/CHESWOLD, DE			AIRPORT NAME:			RNAV			RNAV (GPS) RWY 9, ORIG 12 OCTOBER 2017				AMDT: NONE		
			DELAWARE AIRPARK										DATED		



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
URESJ (FAF)	YEHJU/2.50 NM TO RW09 (TF) (FB) (RNP 0.30)	085.26 / 2.56	
YEHJU/2.50 NM TO RW09	RW09 (MAP) (TF) (FO) (RNP 0.30)	085.26 / 2.50	
RW09 (MAP)	455 MSL (CA)	085.26	
455 MSL	JOSEM (DF) (FO) (RNP 1.00)		2000

QUALITY
16
CHECKED

CITY AND STATE

DOVER/CHESWOLD, DE

ELEVATION: 55

TDZE: 55

AIRPORT NAME:

DELAWARE AIRPARK

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 9, ORIG

12 OCTOBER 2017

SUP:

AMDT: **NONE**

DATED: