

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR OR TACAN STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: 3.90 NM AFTER DANIE INT/HNL 4.46 DME OR AT OBGUE/HNL 0.56 DME FIX								
HNL VORTAC			DANIE INT/HNL 4.46 DME			198.00 / 4.46			4000		CLIMBING RIGHT TURN TO 3000 ON HNL VORTAC R-171 TO ALANA INT/HNL 13.94 DME AND HOLD.								
WUKUL/HNL 14.00 DME CCW (IAF)			KEOKI INT/HNL 9.50 DME (NOPT)			14 DME ARC 018.00 / 4.50 (HNL R-198)			3000										
ALANA INT/HNL 13.94 DME (IAF)			KEOKI INT/HNL 9.50 DME (NOPT)			283.00 / 6.40 (HDG) & 018.00 / 3.50 (HNL R-198)			3000										
KEOKI INT/HNL 9.50 DME (IF)			DANIE INT/HNL 4.46 DME			018.00 / 5.04 (HNL R-198)			1500										
THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 17-08.										ADDITIONAL FLIGHT DATA: HOLD S, RT, 351.00 INBOUND. FAS OBST: 208 SHIPS 211600N/1575800W CHART VDP AT 1.19 DME DISTANCE VDP TO THLD 1.57 NM. CHART HNL R-258 AT WUKUL. CHART CIRCLING ICON.									
1. PT <u>L</u> SIDE OF COURSE <u>198.00</u> OUTBOUND <u>3000</u> FT WITHIN <u>10</u> MILES OF <u>DANIE</u> (IAF)										MAG VAR: 11E EPOCH YEAR: 1990									
2.																			
3. FAF <u>018.00</u> FAF <u>DANIE INT/HNL 4.46 DME</u> DIST FAF TO MAP <u>3.90</u> THLD <u>4.84</u>																			
4. MIN. ALT <u>DANIE 1500</u>																			
8. MSA FROM: <u>HNL VORTAC 360-180 4400, 180-270 4000, 270-360 5300</u>																			
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
S-04R		460	1	451	460	1	451	460	1 1/4	451	460	1 1/2	451						
CIRCLING		640	1	627	760	1	747	760	2 1/4	747	1400	3	1387						
NOTES:																			
CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY.										@ CAT C 800-2 1/4, CAT D 1400-3									
CHART NOTE: CIRCLING RWY 22R NA AT NIGHT.																			
CHART NOTE: CIRCLING NA FOR CATS A AND B NW OF RWYS 8L AND 22R.																			
CHART NOTE: CIRCLING NA FOR CATS C AND D N OF RWY 8L-26R.																			
(CONTINUED ON PAGE 2)																			
CITY AND STATE HONOLULU, HI		ELEVATION: 13 TDZE: 9 AIRPORT NAME:  DANIEL K. INOUE INTL			FACILITY IDENTIFIER: HNL		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR OR TACAN RWY 4R, ORIG-C, 04/27/2017					SUP AMDT DATE							
												ORIG-B 07/15/2002							

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**VOR OR TACAN STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):**

**CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ALANA ON V16 SOUTHEAST BOUND.**

**CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HNL VORTAC ON AIRWAY RADIALS 171 CW 258.**

QUALITY  
4  
CHECKED

CITY AND STATE

HONOLULU, HI

**ELEVATION: 13**

**TDZE: 9**

AIRPORT NAME:

DANIEL K. INOUE INTL

FACILITY  
IDENTIFIER:

HNL

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

**VOR OR TACAN RWY 4R, ORIG-C, 04/27/2017**

SUP:

AMDT: **ORIG-B**

DATED: **07/15/2002**