

<b>RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.			
<b>TERMINAL ROUTES</b>				<b>MISSED APPROACH</b>			
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW04L  CLIMBING RIGHT TURN TO 3000 DIRECT ICEBI AND HOLD.  ADDITIONAL FLIGHT DATA: FAS OBST: 580 AAO 642941N/1491156W 630 AAO 643006N/1491448W CHART VDP AT 1.25 MILES TO RW04L. EKUCO TO RW4L: 3.04/35.			
ROYOY (IAF)	ICEBI (NOPT) (FB)	127.51 / 5.00	3000				
ICEBI (IF/IAF)	EKUCO (FB)	037.60 / 6.25	2000				
"THIS IS A CORRECTED COPY OF THE FORM DATED 04/27/2009 ORIGINALLY PUBLISHED IN TL09-20							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SW ICEBI, RT, 037.60 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 037.78 FAF: EKUCO DIST FAF TO MAP: 4.95 THLD: 4.95 4. MIN. ALT: ICEBI 3000, EKUCO 2000 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____							
				MAG VAR: 21E EPOCH YEAR: 2010			
<b>MINIMUMS</b>							
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N/A	STANDARD @		
CATEGORY ==>	A		B		C		D
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
LNAV MDA	800	1	432	800	1	432	800
CIRCLING	860	1	492	860	1	492	920
NOTES: CHART NOTE: CIRCLING NA W OF RWY 4L-22R. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FAIBANKS INTL ALTIMETER SETTING: INCREASE ALL MDA 100 FT AND LNAV VISIBILITY CAT C/D 1/4 MILE.							
CITY AND STATE		ELEVATION: 368 TDZE: 368		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	
NENANA, AK		AIRPORT NAME: NENANA MUNI				RNAV (GPS) RWY 4L, AMDT 1, 10/22/2009	
						22 OCT 2009	
						SUP: AMDT: ORIG-A	
						DATED 02/17/2006	

QUALITY  
 2  
 CHECKED

## US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	308/30 CW 128/30 (NOPT)	308/10 CW 128/10	6400
2.	308/10 CW 128/10	ICEBI (IF/IAF) (FB)	3000
3.	128/30 CW 218/30	128/10 CW 218/10	4500
4.	128/10 CW 218/10	ROYOY (IAF) (FB)	3000
5.	218/30 CW 308/30	ICEBI (IF/IAF) (FO)	6400

QUALITY  
2  
CHECKED

CITY AND STATE

NENANA, AK

ELEVATION: 368 TDZE: 368

AIRPORT NAME:

NENANA MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 4L, AMDT 1, 10/22/2009

22 OCT 2009

SUP:

AMDT: ORIG-A

DATED: 02/17/2006

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

DATED: 02/17/2006

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	PO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	ICEBI	ICEBI	010	IAF	HF	R	FO		037.6 (059T)	004.0	03000
	ROYOY	ROYOY	010	IAF	IF		FB				
	ROYOY	ICEBI	020		TF		FB	1.0	127.5 (149T)	005.0	03000
		ICEBI	010	FACF	IF		FB				03000
		EKUCO	020	FAP	TF		FB	0.5	037.6 (059T)	006.3	02000
		RW04L	030	MAP	TF		FO	0.3	037.8 (059T)	005.0	00402

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	PO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	ICEBI	040		DF	R	FO	1.0			03000
	ICEBI	050		HM	R	FO	2.0	037.6 (059T)	004.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	EKUCO	N643011.12	W1491501.61	N6430.185	W14915.027
	ICEBI	N642656.88	W1492721.82	N6426.948	W14927.364
	ROYOY	N643111.98	W1493323.51	N6431.200	W14933.392
	RW04L	N643244.19	W1490513.43	N6432.737	W14905.224

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW04L	00367	35

CITY AND STATE  
 NENANA, AK

ELEVATION: 368 TDZE: 368  
 AIRPORT NAME:  
 NENANA MUNI

FACILITY  
 IDENTIFIER:  
 RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
 RNAV (GPS) RWY 4L, AMDT 1, 10/22/2009  
 22 OCT 2009

SUP:  
 AMDT: ORIG-A  
 DATED: 02/17/2006

QUALITY  
 2  
 CHECKED