

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
YALUL (IAF)	UKUCI (NOPT) (FB)	276.97 / 5.00	3000	LNAB: RW19 CLIMB TO 3500 DIRECT NOBDY AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3500. ADDITIONAL FLIGHT DATA: HOLD N, RT, 186.89 INBOUND. CHART FAS OBST: 418 TOWER 354637N/0895752W WORUP TO RW19: 3.04/40.
ZARAM (IAF)	UKUCI (NOPT) (FB)	096.85 / 5.00	3000	
UKUCI (IF/IAF)	WORUP (FB)	186.91 / 6.10	1900	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD N UKUCI, RT, 186.91 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 186.90 FAF: WORUP DIST FAF TO MAP: 5.04 THLD: 5.04
- MIN. ALT: UKUCI 3000, WORUP 1900
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS CLEAR
- MSA FROM:

MAG VAR: 2E EPOCH YEAR: 1985

MINIMUMS

TAKEOFF: <input type="checkbox"/>	STANDARD <input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A <input checked="" type="checkbox"/>												
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAB MDA	620	1	386	620	1	386	620	1	386		NA				
CIRCLING	700	1	466	1060	1 1/4	826	1060	2 1/2	826		NA				

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: USE BLYTHEVILLE MUNI ALTIMETER SETTING; WHEN NOT RECEIVED USE COVINGTON MUNI ALTIMETER SETTING AND INCREASE ALL MDAS 20 FEET.

CITY AND STATE OSCEOLA, AR	ELEVATION: 234 TDZE: 234 AIRPORT NAME: OSCEOLA MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 12 MAR 2009	SUP: AMDT: NONE DATED
--------------------------------------	--	-------------------------------------	--	------------------------------------



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	097/30 CW 277/30 (NOPT)	UKUCI (IF/IAF) (FB)	3000
2.	277/30 CW 007/30	YALUL (IAF) (FB)	3000
3.	007/30 CW 097/30	ZARAM (IAF) (FB)	3000

CITY AND STATE

OSCEOLA, AR

ELEVATION: 234 TDZE: 234

AIRPORT NAME:

OSCEOLA MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 19, ORIG

12 MAR 2009

SUP:

AMDT: NONE

DATED:

QUALITY
3
27-10

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE OSCEOLA, AR	ELEVATION: 234 TDZE: 234 AIRPORT NAME: OSCEOLA MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 12 MAR 2009	SUP:
				AMDT: NONE
				DATED:

QUALITY
3
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	UKUCI	UKUCI	010		HF	R	FB		186.9(189T)	004.0	03000
	YALUL	YALUL	010	IAF	IF		FB				
	YALUL	UKUCI	020		TF		FB	1.0	277.0(279T)	005.0	03000
	ZARAM	ZARAM	010	IAF	IF		FB				
	ZARAM	UKUCI	020		TF		FB	1.0	096.9(099T)	005.0	03000
		UKUCI	010	FACF	IF		FB				03000
		WORUP	020	FAF	TF		FB	0.5	186.9(189T)	006.1	01900
		RW19	030	MAP	TF		FO	0.3	186.9(189T)	005.0	00274

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	NOBDY	040		DF		FO	1.0			03500
	NOBDY	050		HM	R	FO	2.0	186.9(189T)	004.0	03500

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	NOBDY	N353351.74	W0900203.80	N3533.862	W09002.063
	UKUCI	N355248.02	W0895825.76	N3552.800	W08958.429
	WORUP	N354645.68	W0895935.48	N3546.761	W08959.591
	YALUL	N355201.33	W0895221.11	N3552.022	W08952.352
	ZARAM	N355334.40	W0900430.53	N3553.573	W09004.509
	RW19	N354146.69	W0900032.87	N3541.778	W09000.548

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW19	00234	40

CITY AND STATE
OSCEOLA, AR

ELEVATION: 234 TDZE: 234
 AIRPORT NAME:
 OSCEOLA MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 19, ORIG
 12 MAR 2009

SUP:
 AMDT: NONE
 DATED: