

**Federal Aviation
Administration**

Transmittal Letter 18-16

June 15, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
19-Jul-18	GA	Washington	Washington-Wilkes County	7/2604	6/7/18	RNAV (GPS) RWY 31, Amdt 1A

AIRAC Date: 19 JULY 2018

FDC **7/2604** IY IAP WASHINGTON-WILKES COUNTY, Washington, GA. RNAV (GPS) RWY 31, AMDT 1A... LNAV MDA 1200/HAT 560 CATS A/B/C, VISIBILITY CAT C 1-5/8. CIRCLING MDA 1200/HAA 554 CATS A/B/C, VISIBILITY CAT C 1-5/8. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ATHENS ALTIMETER SETTING AND INCREASE LPV DA TO 1078, LNAV/VNAV DA TO 1135, AND ALL MDA 100 FEET; INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS, LNAV CAT C, AND CIRCLING CAT C VISIBILITY TO 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ATHENS ALTIMETER SETTING: INCREASE LPV DA TO 1078 FEET, LNAV/VNAV DA TO 1135 FEET, AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 100 FEET AND VISIBILITY CAT C 1/4 SM. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. DELETE NOTE: RWY 31 STRAIGHT-IN AND CIRCLING NA AT NIGHT. 34:1 IS CLEAR. THIS IS RNAV (GPS) RWY 31, AMDT 1B. 1706291625-PERM