

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION															
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW23 CLIMB TO 2000 DIRECT CALOO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 051.09 INBOUND. CHART FAS OBST: 318 TOWER 263755N/0814836W CHART FAS OBST: 168 TOWER 263542N/0815146W DISTANCE TO THLD FROM 266 HATH: 0.66 NM. WAAS CHANNEL # 69424 REFERENCE PATH ID: W23A LTP HAE: -19.2 M											
TIRTE (IAF)	APASY (FB)	291.00 / 24.92	2500												
LBV VORTAC (IAF)	APASY (FB)	250.99 / 18.29	2500												
VASES (IAF)	APASY (FB)	186.55 / 5.71	2500												
APASY (IF)	GLUMM (FB)	230.93 / 6.10	1600												
GLUMM (FAF)	EBAXE/2.00 NM TO RW23 (FB)	230.89 / 2.80													
EBAXE/2.00 NM TO RW23	RW23 (MAP) (FO)	230.87 / 2.00													
(SEE FORM 8260-10)															
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)				MAG VAR: 3W EPOCH YEAR: 1990											
2. PROFILE STARTS AT APASY															
3. FAC: 230.89 FAF: GLUMM DIST FAF TO MAP: 4.80 THLD: 4.80															
4. MIN. ALT: APASY 2500, GLUMM 1600, EBAXE/2.00 NM TO RW23 700'															
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:															
6. MIN GS INCPT: 1600 GS ALT AT: GLUMM 1600 OM: MM: IM:															
7. GS ANGLE: 3.00 TCH: 55.0 34:1 IS NOT CLEAR															
8. MSA FROM: RW23 2600															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A STANDARD											
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	282	1	266	282	1	266	282	1	266		NA				
LNAV/VNAV DA	338	1	322	338	1	322	338	1	322		NA				
LNAV MDA	420	1	404	420	1	404	420	1 1/8	404		NA				
CIRCLING	540	1	523	540	1	523	540	1 1/2	523		NA				
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT TIRTE ON V599 EASTBOUND AND ARRIVALS AT VASES ON (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 17 THRE: 16		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
FORT MYERS, FL		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 23, ORIG				AMDT: NONE					
		PAGE FIELD				25 AUG 2011				DATED					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW23 (MAP)	282 MSL	230.87	
282 MSL	CALOO (FO)		2000

NOTES, (CONT.):

V521 NORTHBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON LBV VORTAC AIRWAY RADIALS 228 CW 334.

*LNAV ONLY

CITY AND STATE

FORT MYERS, FL

ELEVATION: 17

THRE: 16

AIRPORT NAME:

PAGE FIELD

**FACILITY
IDENTIFIER:**

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

RNAV (GPS) RWY 23, ORIG

25 AUG 2011

SUP:

AMDT: NONE

DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KFMY
RUNWAY RW23
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W23A
LTP/FTP LATITUDE 263527.9425N
LTP/FTP LONGITUDE 0815126.8770W
LTP/FTP ELLIPSOIDAL HEIGHT -00192
FPAP LATITUDE 263427.9800N
FPAP LONGITUDE 0815240.5700W
THRESHOLD CROSSING HEIGHT (TCH) 00055.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0920
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

4188DEC3

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K7
LTP ORTHOMETRIC HEIGHT +00049
FPAP ORTHOMETRIC HEIGHT +00049

CITY AND STATE

FORT MYERS, FL

ELEVATION: 17

THRE: 16

AIRPORT NAME:

PAGE FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 23, ORIG

25 AUG 2011

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
A
CHECKED

CITY AND STATE FORT MYERS, FL	ELEVATION: 17 THRE: 16	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 23, ORIG 25 AUG 2011	SUP:
	AIRPORT NAME:			AMDT: NONE
	PAGE FIELD			DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KFMYK7GRW23 0064062309 N26352794W081512688-0100 -0019200016039955150R

SUSAP	KFMYK7PR23	RW23	001	0000W23A0N2635279425W08151268770-001920300N2634279800W08152405700106750920000550F4005004188DEC3
SUSAP	KFMYK7PR23	RW23	002E	+00049+00049LEV 69424

SUSAP KPMYK7SRW23 K7PG	0	18018002625	M
------------------------	---	-------------	---

QUALITY
4
CHECKED

ELEVATION: 17 THRE: 16
AIRPORT NAME:
PAGE FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 23, ORIG
25 AUG 2011

SUP:	
AMDT:	NONE
DATED:	