

U.S. DEPARTMENT of TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

DEPARTURE PROCEDURES / TAKEOFF MINIMUMS

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

COORDINATED

ATA
☐

AAT
☐

ALPA
☐

APA
☐

AOPA
☒

NBAA
☒

OTHER (specify)
☒

CLE ARTCC, CAK ATCT, AMGR

TAKEOFF MINIMUMS:

RWY 10: STANDARD

RWY 28: 300-1



IFR DEPARTURE PROCEDURE:

TAKEOFF OBSTACLES:

RWY 28: 1134 TREE 405234/815352

DEPARTURE OBSTACLES:

*EFFECTIVE CONCURRENT WITH GPS RWY 28, AMDT. NO. 1.

DEVELOPED BY		APPROVED BY	
SIGNATURE:  BRADLEY W. RUSH (B. N. MCCULLAR)	DATE: 01/02/98 FIFO: AVN-140	SIGNATURE:  JOSEPH E. ROONEY	DATE: MAR 12 1998 FIFO: AVN-140
CITY AND STATE WOOSTER, OH	AIRPORT WAYNE COUNTY	EFFECTIVE •	AMDT. NO. 1