

# DEPARTURE PROCEDURES/TAKEOFF MINIMUMS

Basic

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED WITH	<input checked="" type="checkbox"/>	AAT	<input type="checkbox"/>	ATA	<input type="checkbox"/>	ALPA	<input type="checkbox"/>	AOPA	<input type="checkbox"/>	NBAA	<input type="checkbox"/>	APA	<input checked="" type="checkbox"/>	OTHER (Specify) AVN-220, AGL-220, ZOB ARTCC, FNT ATCT, AMGR
------------------	-------------------------------------	-----	--------------------------	-----	--------------------------	------	--------------------------	------	--------------------------	------	--------------------------	-----	-------------------------------------	---

## TAKEOFF MINIMUMS:



Rwys 9, 14, 27 and 32 300-1.  
Rwys 18 and 36 Standard.

## TAKEOFF OBSTACLES:

Rwy 14: 930 Trees 430346/831557.  
Rwy 32: 930 Trees 430418/831640.  
Rwy 9: 930 Trees 430354/831600.  
Rwy 27: 900 Bldg 430354/831634.

\*Concurrent with VOR-A, Amdt. 12.

50 Jun 86

DEVELOPED BY		APPROVED BY	
SIGNATURE 	DATE 3/7/86 FIFO BTL	SIGNATURE 	DATE 3/7/86
CITY AND STATE Lapeer, MI.	AIRPORT Dupont-Lapeer	EFFECTIVE DATE *	AMDT. NO. 3