

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)  
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<b>CITY, STATE</b>	<b>AIRPORT</b>	<b>EFFECTIVE DATE</b>	<b>AMDT NO</b>
FINDLAY, OH	FINDLAY	6 DECEMBER 2018	1

**TAKEOFF MINIMUMS:**

RWY 7, 18, 36: STANDARD

RWY 25: 300-1 5/8 OR STANDARD WITH MINIMUM CLIMB OF 210 FT PER NM TO 1100, OR ALTERNATIVELY WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT PER NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1400 FEET PRIOR TO DER.

**TEXTUAL DEPARTURE PROCEDURES:**

**VISUAL CLIMB OVER AIRPORT:**

**TAKEOFF OBSTACLE NOTES:**

NOTE RWY 07: ROAD WITH VEHICLES BEGINNING 55 FEET FROM DER, 308 FEET RIGHT OF CENTERLINE, UP TO 15 FEET AGL/821 FEET MSL.

WALL, POLE BEGINNING 121 FEET FROM DER, 48 FEET LEFT OF CENTERLINE, UP TO 10 FEET AGL/816 FEET MSL.

TREE, ROAD WITH VEHICLES, POLE BEGINNING 154 FEET FROM DER, 69 FEET RIGHT OF CENTERLINE, UP TO 32 FEET AGL/838 FEET MSL.

ROAD WITH VEHICLES BEGINNING 210 FEET FROM DER, 1 FEET LEFT OF CENTERLINE, UP TO 15 FEET AGL/821 FEET MSL.

TREES BEGINNING 279 FEET FROM DER, 45 FEET RIGHT OF CENTERLINE, UP TO 33 FEET AGL/839 FEET MSL.

TREE, POLE, BUILDING BEGINNING 338 FEET FROM DER, 33 FEET LEFT OF CENTERLINE, UP TO 26 FEET AGL/832 FEET MSL.

TREE 1715 FEET FROM DER, 959 FEET RIGHT OF CENTERLINE, 54 FEET AGL/860 FEET MSL.

TREES BEGINNING 1846 FEET FROM DER, 407 FEET RIGHT OF CENTERLINE, UP TO 64 FEET AGL/870 FEET MSL.

BUILDING 2374 FEET FROM DER, 1054 FEET RIGHT OF CENTERLINE, 110 FEET AGL/916 FEET MSL.

BUILDING, TREE, WIND INDICATOR BEGINNING 2417 FEET FROM DER, 109 FEET RIGHT OF CENTERLINE, UP TO 121 FEET AGL/927 FEET MSL.

NOTE RWY 18: TREE 2786 FEET FROM DER, 150 FEET LEFT OF CENTERLINE, 876 FEET MSL.

NOTE RWY 25: FENCE, VEGETATION BEGINNING 26 FEET FROM DER, 141 FEET LEFT OF CENTERLINE, UP TO 6 FEET AGL/799 FEET MSL. ROAD WITH VEHICLES BEGINNING 133 FEET FROM DER, 108 FEET RIGHT OF CENTERLINE, UP TO 15 FEET AGL/803 FEET MSL.

SIGN, TREE, POLE BEGINNING 473 FEET FROM DER, 421 FEET RIGHT OF CENTERLINE, UP TO 64 FEET AGL/852 FEET MSL.

TREE, POLE, ROAD WITH VEHICLES BEGINNING 785 FEET FROM DER, 397 FEET RIGHT OF CENTERLINE, UP TO 15 FEET AGL/802 FEET MSL.

ELEVATOR, TREE BEGINNING 1824 FEET FROM DER, 295 FEET RIGHT OF CENTERLINE, UP TO 78 FEET AGL/869 FEET MSL.

TREES BEGINNING 2207 FEET FROM DER, 454 FEET RIGHT OF CENTERLINE, UP TO 88 FEET AGL/876 FEET MSL.

ELEVATOR 1.2 NM FROM DER, 1040 FEET RIGHT OF CENTERLINE, 206 FEET AGL/999 FEET MSL.

ELEVATOR 1.3 NM FROM DER, 1114 FEET RIGHT OF CENTERLINE, 207 FEET AGL/1000 FEET MSL.

NOTE RWY 36: POLE 1191 FEET FROM DER, 742 FEET RIGHT OF CENTERLINE, 39 FEET AGL/835 FEET MSL.

TREE 1559 FEET FROM DER, 498 FEET LEFT OF CENTERLINE, 51 FEET AGL/847 FEET MSL.

**CONTROLLING OBSTACLES:**

RWY 25: 999 FEET MSL ELEVATOR 410022.30N/0834232.98W (CLIMB GRADIENT) (CLIMB-TO ALTITUDE), 1000 FEET MSL ELEVATOR 410022.80N/0834233.96W (CEILING) (VISIBILITY)

**REMARKS:**

**FLIGHT INSPECTED BY:**

JAMES ONIEAL

*Digitally signed by*  
**DAVID TEFFETELLER**  
Aug 31, 2018

**OFFICE SYMBOL:**  
FICO

**DATE:**  
8/27/18

**DEVELOPED BY:**

ROBERT GRIM

*Digitally signed by*  
**ROBERT GRIM**  
Jul 13, 2018

**OFFICE SYMBOL:**  
AJV-5431

**DATE:**  
07/13/2018

**APPROVED BY:**

PATRICK MULQUEEN

*Digitally signed by*  
**DAVID TEFFETELLER**  
Aug 31, 2018

**OFFICE SYMBOL:**  
AJV-5430

**DATE:**

**REQUIRED EFFECTIVE DATE:**

ROUTINE

QUALITY  
3  
CHECKED

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)  
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

**CITY, STATE**  
FINDLAY, OH

**AIRPORT**  
FINDLAY

<b>EFFECTIVE DATE</b>	<b>AMDT NO</b>
6 DECEMBER 2018	1

**COORDINATED WITH:**

<b>A4A</b>	<b>ALPA</b>	<b>AOPA</b>	<b>APA</b>	<b>HAI</b>	<b>NBAA</b>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

**OTHER:**  
TOLEDO APP/DEP CON, AMGR

**CHANGES - REASONS:**

1. TAKEOFF MINIMUMS RWY 25 CHANGED FROM STANDARD TO 300-1 5/8 OR STANDARD WITH MINIMUM CLIMB OF 210 FT PER NM TO 1100, OR ALTERNATIVELY WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT PER NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1400 FEET PRIOR TO DER - PER TARGETS EVALUATION (39-066499 - 999 FEET MSL ELEVATOR 410022.30N/0834232.98W, 39-030657 - 1000 FEET MSL ELEVATOR 410022.80N/0834233.96W) AND PREVIOUS EVALUATION/NOTAM.
2. UPDATED TAKEOFF NOTES - IAW 8260.46F APPENDIX D, SECTION 1, PARA 9A.

