

**Federal Aviation  
Administration**

**Transmittal Letter 18-21**

**August 24, 2018**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
11-Oct-18	IL	Litchfield	Litchfield Muni	8/6818	8/14/18	RNAV (GPS) RWY 18, Orig-A

**AIRAC Date: 11 OCTOBER 2018**

FDC 8/6818 3LF IAP LITCHFIELD MUNI, Litchfield, IL. RNAV (GPS) RWY 18, ORIG-A... DELETE NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE TAYLORVILLE ALTIMETER SETTING AND INCREASE ALL DA'S 73 FEET AND ALL MDA'S 80 FEET. DELETE NOTE: DME/DME RNP-0.3 NA. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. CHART NOTE: RWY 18 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TAYLORVILLE ALTIMETER SETTING AND INCREASE ALL DA 73 FEET AND ALL MDA 80 FEET. INCREASE LPV ALL CATS VISIBILITY TO 1 1/8 SM AND LNAV CAT C VISIBILITY TO 1 3/8 SM. PBN REQUIREMENTS NOTE: RNP APCH. LNAV CAT A/B/C MDA 1120/HAT 435. VDP 1.3 NM TO RWY 18. 20:1 IS CLEAR. 34:1 IS NOT CLEAR. THIS IS RNAV (GPS) RWY 18, ORIG-B. 1807171640-PERM