

**Federal Aviation
Administration**

Transmittal Letter 19-13

MAY 3, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
6/20/2019	MI	Alpena	Alpena County Rgnl	9/1687	4/3/2019	RNAV (GPS) RWY 1, Orig-B

AIRAC Date: 20 JUNE 2019

FDC 9/1687 APN IAP ALPENA COUNTY RGNL, Alpena, MI. RNAV (GPS) RWY 1, ORIG-B... CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROGERS CITY ALTIMETER SETTING; INCREASE ALL LPV DAS TO 1029 FEET, LNAV/VNAV DAS TO 1084 FEET AND ALL MDAS 60 FEET; INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS AND LNAV CATS C AND D VISIBILITY 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROGERS CITY ALTIMETER SETTING AND INCREASE ALL DA 55 FEET AND ALL MDA 60 FEET AND INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS AND LNAV CATS C AND D VISIBILITY 1/4 MILE. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WHOOP ON V45 SOUTHBOUND, AND ARRIVALS AT SPARR ON V420 WESTBOUND, AND ARRIVALS AT RABBO ON V78 NORTHWEST BOUND. DELETE PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WHOOP VIA V45 SOUTHBOUND, FOR ARRIVALS AT SPARR VIA V420 WESTBOUND AND FOR ARRIVALS AT RABBO VIA V78 NORTHWEST BOUND. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LPV ALL CATS VISIBILITY TO 1 SM. DELETE NOTE: FOR INOPERATIVE MALSR, INCREASE LPV ALL CATS VISIBILITY TO 1. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. MISSED APPROACH: CLIMB TO 3500 DIRECT HIMVO AND ON TRACK 307.05 TO RABBO AND HOLD. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 48C. DELETE NOTE: FOR THIS IS RNAV (GPS) RWY 1, ORIG-C. UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 48C (118F). THIS IS RNAV (GPS) RWY 1, ORIG-C. 1903041629-PERM