

DEPARTURE PROCEDURES / TAKEOFF MINIMUMS

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED WITH:

ATA ☒ AAT ☐ ALPA ☒ APA ☒ AOP ☒ NBA ☒ OTHER (specify) ☒ AVN-220,AEA-220,ZNY,IPT FSS,PHL APCH,ARPT MGR.

TAKEOFF MINIMUMS:

RWY 10 300-1 OR STANDARD WITH MINIMUM CLIMB OF 290' NM TO 500.
RWY 28 500-2

IFR DEPARTURE PROCEDURE:



RWY 28 CLIMB RUNWAY HEADING TO 800 BEFORE TURNING ON COURSE.

TAKEOFF OBSTACLES:

RWY 10: 449 TREES 401426/753226

DEPARTURE OBSTACLES:

RWY 28: 769 TOWERS 401336/753514

DEVELOPED BY		APPROVED BY	
SIGNATURE:  JAMES P. HAUGH	DATE: AUG 30 1994 FIFO: ACY	SIGNATURE:  DENNIS DADE, ACTING MANAGER	DATE: AUG 30 1994 FIFO: ACY
CITY AND STATE POTTSTOWN,PA	AIRPORT POTTSTOWN-LIMERICK	EFFECTIVE DATE ROUTINE	AMDT. NO. 2