

**Federal Aviation
Administration**

Transmittal Letter 12-24

OCTOBER 12, 2012

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
15-Nov-12	WV	Martinsburg	Eastern WV Rgnl/Shepherd Fld	2/8018	09/26/12	RNAV (GPS) RWY 26, ORIG

AIRAC Date: 15 NOVEMBER 2012

FDC 2/8018 MRB FI/P IAP EASTERN WV RGNL/SHEPHERD FLD, MARTINSBURG, WV.
RNAV (GPS) RWY 26, ORIG... LNAV VIS CAT C 3/4. CIRCLING HAA CAT A 455, CATS B/C
515, CAT E 1575. CIRCLING CAT D MDA 1380/ HAA 815. VIS CAT D 2 3/4. CHANGE
MISSED APPROACH INSTRUCTIONS TO READ: CLIMB TO 4100 DIRECT JOSRU AND
HOLD, CONTINUE CLIMB-IN-HOLD TO 4100. CHANGE ALTIMETER NOTE TO READ:
WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HAGERSTOWN ALTIMETER
SETTING AND INCREASE ALL DA 70 FEET AND ALL MDA 80 FEET, INCREASE
LNAV/NAV ALL CATS, LNAV CATS C,D,E AND CIRCLING CAT D VISIBILITIES 1/4 MILE.
CHANGE UNCOMPENSATED NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV
SYSTEMS, LNAV/VNAV NA BELOW -16C(4F) OR ABOVE 54C(130F). ALTERNATE
MINIMUMS: STANDARD; EXCEPT CAT D 900-2 3/4, CAT E 1600-3. NA WHEN LOCAL
WEATHER NOT AVAILABLE. CHART AIRPORT ELEV: 565. THIS IS RNAV (GPS) RWY 26,
ORIG-A.