

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAB: RW23
DIRPE (IF/IAF)	ZURDA (FB)	224.81 / 5.17	2000	
				CLIMB TO 3000 DIRECT WOKUS AND VIA TRACK 229.9 TO AWISA AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD SW, LT, 049.84 INBOUND. FAS OBST: 779 AAO 402223N/0750608W ZURDA TO RW23: 3.04/40.

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD NE DIRPE, RT, 224.81 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 229.47 FAF: ZURDA DIST FAF TO MAP: 4.86 THLD: 4.86
- MIN. ALT: DIRPE 3000, ZURDA 2000
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM: RW23 2600

MAG VAR: 12W

EPOCH YEAR: 1995

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A			STANDARD @							
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	1040	1	646	1040	1	646		NA			NA					
CIRCLING	1040	1	646	1040	1	646		NA			NA					

NOTES:

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PROFILE NOTE: VGSi AND DESCENT ANGLES NOT COINCIDENT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TRENTON ALTIMETER SETTING AND INCREASE

SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
2
CHECKED

CITY AND STATE DOYLESTOWN, PA	ELEVATION: 394 TDZE: 394 AIRPORT NAME: DOYLESTOWN	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 23, AMDT 1 08 APR 2010	SUP: AMDT: ORIG DATED 11/25/2004
----------------------------------	---	---------------------------------	--	--

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.
ALL MDA 60 FEET.

QUALITY
2
CHECKED

CITY AND STATE DOYLESTOWN, PA	ELEVATION: 394 TDZE: 394	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 23, AMDT 1 08 APR 2010	SUP:
	AIRPORT NAME: DOYLESTOWN			AMDT: ORIG
	DATED: 11/25/2004			

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

PAGE 3 OF 3 PAGES