U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
HINDU INT/PTW 10.00 DME/RADAR (IF/IAF)	ZOBAD INT/PTW 5.00 DME/RADAR	211.00 / 5.00 (PTW R-031)	2300

MISSED APPROACH

MAP: PTW 1.15 DME FIX

CLIMBING LEFT TURN TO 2300 VIA PTW VORTAC R-031 TO ZOBAD INT/PTW 5.00 DME/RADAR AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD NE, LT, 211.00 INBOUND.
CHART FAS OBST: 701 TREE 401615N/0753257W
FAC CROSSES RWY 28 THLD
CHART CIRCLING ICON

1. PT NA SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. PROFILE STARTS AT HINDU INT/PTW 10.00 DME/RADAR
3. FAC 211.00 FAF ZOBAD INT/PTW 5.00 DME/RADAR DIST FAF TO MAP 3.85 THLD ____
4. MIN. ALT HINDU 2700, ZOBAD 2300
8. MSA FROM: PTW VOR/DME 2900

MAG VAR: 9W EPOCH YEAR: 1965

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: NA CIRCLING: STANDARD @

CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	960	1	652	960	1	652		NA			NA				

NOTES:

CHART NOTE: CIRCLING NA SOUTH OF RWY 10 AND 28 OF RWY.
CHART PLANVIEW NOTE: RADAR REQUIRED.
CHART NOTE: WHEN LOCAL ALTIMETER NOT RECEIVED, USE WINGS FIELD ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY 6 CHECKED

CITY AND STATE	ELEVATION: 308 TDZE:	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP
POTTSTOWN, PA	AIRPORT NAME: HERITAGE FIELD	PTW	VOR/DME-A, AMDT 4 29 MAY 2014	AMDT 3C
				DATE 5/2/2013