

**Federal Aviation
Administration**

Transmittal Letter 18-21

August 24, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
11-Oct-18	MI	Grayling	Grayling AAF	8/9448	8/9/18	RNAV (GPS) RWY 14, Orig-B

AIRAC Date: 11 OCTOBER 2018

FDC 8/9448 GOV IAP GRAYLING AAF, Grayling, MI. RNAV (GPS) RWY 14, ORIG-B...
LNAV HAT 546 ALL CATS, VIS CAT C 1 5/8. CIRCLING CAT A/B/C HAA 562, VIS
CAT C 1 5/8, CAT D HAA 602. CHART TDZE 1154. CHART APT ELEV 1158. CHART
NOTE: CIRCLING RWY 5, 23, 32 NA AT NIGHT. CHART NOTE: RWY 14
HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT
AUTHORIZED. DELETE NOTE: PROCEDURE NA AT NIGHT FOR CAT C/D
AIRCRAFT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED
USE HOUGHTON LAKE ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET
AND VISIBILITY CAT C 1/8 SM. DELETE NOTE: WHEN LOCAL ALTIMETER
SETTING NOT RECEIVED, USE HOUGHTON LAKE ALTIMETER SETTING AND
INCREASE ALL MDA 60 FEET, INCREASE LNAV CAT C AND D AND CIRCLING
CAT C VISIBILITY 1/4 MILE. DELETE NOTE: DME/DME RNP-0.3 NA. PBN
REQUIREMENTS NOTE: RNP APCH. THIS IS RNAV (GPS) RWY 14, ORIG-C.
1807191726-PERM