



## U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV

## STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA:

FROM	TO	ALTITUDE
1. 317/30 CW 137/30	SEYOP WP (NoPT) (IF/IAF)	3500
2. 137/30 CW 227/30	RITOC WP (IAF)	3500
3. 227/30 CW 317/30	YIPUD WP (IAF)	3500

CITY AND STATE

HIBBING, MN

ELEVATION: 1353 TDZE: 1350

AIRPORT NAME:

CHISHOLM-HIBBING

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

AUG - 5 2004

RNAV (GPS) RWY 4, ORIG

SUP:

AMDT: NONE

DATED: