

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23					Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES					MISSED APPROACH										
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 5.10 MILES AFTER GINGS INT/ROD 11 DME OR AT 16.10 DME MISSED APPROACH: CLIMB TO 2800 THEN LEFT TURN DIRECT ROD VORTAC AND HOLD ADDITIONAL FLIGHT DATA: FAS OBST 1230 TREES 400926/835137											
ROD VORTAC NO PT FOR ARRIVALS ON ROD	GINGS INT/ROD 11 DME VORTAC AIRWAY RADIALS 273	130.39/11.00 CW 023	2800												
1. PT <u>NA</u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. <u>HOLD NW ROD VORTAC, RT, 130.39 INBOUND, 2800 FT IN LIEU OF PT (IAF)</u> 3. FAC <u>130.39</u> FAF <u>GINGS INT</u> DIST FAF TO MAP <u>5.10</u> THLD <u>-</u> 4. MIN. ALT <u>ROD VORTAC 2800, GINGS INT 2800</u> 8. MSA FROM: <u>ROD VORTAC 3000, (30 NM)</u>					MAG VAR: 5W EPOCH YEAR: 95										
MINIMUMS															
TAKEOFF:	<input checked="" type="checkbox"/>	STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD						
CATEGORY ==>	A		B			C			D		E				
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA
CIRCLING	1580	1	512	1580	1	512	1580	1 1/2	512		NA				
NOTES:															
CITY AND STATE			ELEVATION: 1068 TDZE:			FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:			SUP				
URBANA, OH			AIRPORT NAME: GRIMES FIELD			ROD		SEP 30 2004 VOR-A, AMDT 5C			AMDT 5B				
											DATE 03/21/03				