

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW19 LNAV: RW19
NEPRE (IAF)	OVOKY (NOPT) (FB)	242.86 / 8.00	3300	CLIMB TO 3500 DIRECT ULEHI AND HOLD.
OVOKY (IF/IAF)	KAPGE (FB)	190.06 / 7.04	2400	
KAPGE (FAF)	SAGJU/2.30 NM TO RW19 (FB)	190.04 / 3.38		
SAGJU/2.30 NM TO RW19	RW19 (MAP) (FO)	190.03 / 2.30		
RW19 (MAP)	953 MSL	190.03	3500	ADDITIONAL FLIGHT DATA: HOLD S, LT, 010.00 INBOUND. CHART FAS OBST: 729 TREE 340211N/0934944W WAAS CHANNEL # 65921 REFERENCE PATH ID: W19A KAPGE TO RW19: 3.00/40 LTP HAE: 140.2 M
953 MSL	ULEHI (FO)			

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD N OVOKY, RT, 190.06 INBOUND, 3300 FT. IN LIEU OF PT (IAF)
- FAC: 190.04 FAF: KAPGE DIST FAF TO MAP: 5.68 THLD: 5.68
- MIN. ALT: OVOKY 3300, KAPGE 2400, SAGJU/2.30 NM TO RW19 1320
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM: RW19 3600

MAG VAR: 2E

EPOCH YEAR: 2010

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: N A X

CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	1080	1	530	1080	1	530		NA			NA				
LNAV MDA	1080	1	530	1080	1	530		NA			NA				
CIRCLING	1100	1	547	1100	1	547		NA			NA				

NOTES:

CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 01 NA AT NIGHT.

CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 19 PROCEDURE NA AT NIGHT.

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

(SEE FORM 8260-10)

CITY AND STATE	ELEVATION: 553	THRE: 550	FACILITY	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
NASHVILLE, AR	AIRPORT NAME:		IDENTIFIER:	RNAV (GPS) RWY 19, ORIG	AMDT: NONE
	HOWARD COUNTY		RNAV	9 FEB 2012	QUALITY DATED

QUALITY
CHECKED
DATE

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD

INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT NEPRE ON V124 NORTHEAST BOUND.

CHART NOTE: USE DE QUEEN ALTIMETER SETTING; WHEN NOT RECEIVED, USE TEXARKANA ALTIMETER SETTING AND INCREASE ALL MDA 20 FT.



CITY AND STATE

NASHVILLE, AR

ELEVATION: 553

THRE: 550

AIRPORT NAME:

HOWARD COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 19, ORIG

9 FEB 2012

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	M77
RUNWAY	RW19
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W19A
LTP/FTP LATITUDE	340009.3300N
LTP/FTP LONGITUDE	0935012.1200W
LTP/FTP ELLIPSOIDAL HEIGHT	+01402
FPAP LATITUDE	335842.0300N
FPAP LONGITUDE	0935034.4500W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

113674D7

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+01675
FPAP ORTHOMETRIC HEIGHT	+01675



CITY AND STATE NASHVILLE, AR	ELEVATION: 553	THRE: 550	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 9 FEB 2012	SUP:
	AIRPORT NAME:	HOWARD COUNTY			AMDT: NONE
					DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP M77 K4FR19	ANEPRE	010NEPREK4EA0E	A	IF						18000		A JS	
SUSAP M77 K4FR19	ANEPRE	020OVOKYK4EA0EE	B	010TF		24290080		+ 03300				A JS	
SUSAP M77 K4FR19	AOVOKY	010OVOKYK4EA0EE	AR	HF		19010040		+ 03300	18000			A JS	
SUSAP M77 K4FR19	R	010OVOKYK4EA0E	I	IF				+ 03300	18000			A JS	
SUSAP M77 K4FR19	R	020KAPGEK4EA1E	F	051TF		19010070		+ 02400			RW19	K4PGA JS	
SUSAP M77 K4FR19	R	020KAPGEK4EA2WALP			N		ALNAV					JS	
SUSAP M77 K4FR19	R	021SAGJUK4EA0E	S	031TF		19000034		V 0132001322		-300		A JS	
SUSAP M77 K4FR19	R	030RW19 K4PG0GY	M	031TF		19000023		00590		-300		A JS	
SUSAP M77 K4FR19	R	040	0	M	CA	1900		+ 00953				A JS	
SUSAP M77 K4FR19	R	050ULEHIK4EA0EY		DF				+ 03500				A JS	
SUSAP M77 K4FR19	R	060ULEHIK4EA0EE	L	HM		01000040		+ 03500				A JS	

[illegible][illegible]

QUALITY
8
CHECKED

CITY AND STATE NASHVILLE, AR	ELEVATION: 553 THRE: 550 AIRPORT NAME: HOWARD COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 9 FEB 2012	SUP:
				AMDT: NONE
				DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
8
CHECKED

CITY AND STATE NASHVILLE, AR	ELEVATION: 553	THRE: 550	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 9 FEB 2012	SUP:	
	AIRPORT NAME:				AMDT:	NONE
	HOWARD COUNTY				DATED:	