

**PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
 .....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11-Mar-10	IN	Marion	Marion Muni	0/2159	1/22/10	VOR RWY 15, AMDT 10

**FDC 0/2159** MZZ FI/P MARION MUNI, MARION, IN. VOR RWY 15, AMDT 10...S-15 MDA 1500/HAT 642 ALL CATS. VISIBILITY CAT C 1 3/4, CAT D 2. CIRCLING MDA 1500/HAA 641 ALL CATS. VISIBILITY CAT C 1 3/4, CAT D 2. CHANGE PROFILE NOTE TO READ: (ASTERISK) 1600 WHEN USING FORT WAYNE ALTIMETER SETTING. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FORT WAYNE ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET, INCREASE S-15 AND CIRCLING CAT B VISIBILITY 1/4 MILE, CAT C AND D 1/2 MILE. BUCRA FIX MINIMUMS: INCREASE S-15 CAT C AND D VISIBILITY 1/4 MILE. THIS IS VOR RWY 15, AMDT 10A.