

<b>RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
<b>TERMINAL ROUTES</b>						<b>MISSED APPROACH</b>					
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LNAV/VNAV: DA LNAV: RW29			
JKALL (IAF)		IGIDY (NOPT) (FB)		022.07 / 5.00		3300		CLIMB TO 3400 DIRECT NUTFO AND HOLD.			
HORPU (IAF)		IGIDY (NOPT) (FB)		202.17 / 5.00		3300					
IGIDY (IF/IAF)		IPREZ (FB)		292.12 / 6.10		3100					
IPREZ (FAF)		RW29 (MAP) (FO)		292.02 / 4.51							
RW29 (MAP)		2007 MSL		292.02				ADDITIONAL FLIGHT DATA: HOLD W, RT, 111.76 INBOUND. CHART FAS OBST: 1800 TWR 474632N/0995501W FAS OBST: 1844 AAO 474542N/0995026W DISTANCE TO THLD FROM 512 HAT: 1.48 NM.			
2007 MSL		NUTFO (FO)				3400					

  

1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF)									
2. HOLD E IGIDY, RT, 292.12 INBOUND, 3300 FT. IN LIEU OF PT (IAF)									
3. FAF: <u>292.02</u> FAF: <u>IPREZ</u> DIST FAF TO MAP: <u>4.51</u> THLD: <u>4.51</u>									
4. MIN. ALT: <u>IGIDY 3300, IPREZ 3100</u>									
5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u>									
6. MIN GS INCPT: <u>3100</u> GS ALT AT: <u>IPREZ 3100</u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u>									
7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS NOT CLEAR									
8. MSA FROM: <u>      </u>									

MAG VAR: 8E      EPOCH YEAR: 2000

  

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A <input checked="" type="checkbox"/> X								
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV/VNAV DA	2119	1 3/4	512	2119	1 3/4	512	2119	1 3/4	512		NA				
LNAV MDA	2100	1	493	2100	1	493	2100	1 1/4	493		NA				
CIRCLING	2100	1	493	2100	1	493	2100	1 1/2	493		NA				

  

NOTES:  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
 CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.  
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C (0F) OR ABOVE 54C (130F).  
 (SEE FORM 8260-10)

  

CITY AND STATE <div style="text-align: center;">HARVEY, ND</div>		ELEVATION: 1607      TDZE: 1607 AIRPORT NAME: <div style="text-align: center;">HARVEY MUNI</div>		FACILITY IDENTIFIER: <div style="text-align: center;">RNAV</div>		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <div style="text-align: center;">RNAV (GPS) RWY 29, ORIG-A 28 JUL 2011</div>		SUP: AMDT:      ORIG DATED      09/23/2010	
---	--	--	--	---	--	--	--	--	--

 QUALITY  
4  
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: CIRCLING TO RWY 11 NA AT NIGHT.

CHART NOTE: BARO-VNAV NA WHEN USING DEVIL'S LAKE ALTIMETER SETTING.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DEVIL'S LAKE ALTIMETER SETTING AND INCREASE ALL DA 127 FT, AND ALL MDA 140 FT; INCREASE LNAV/VNAV VISIBILITY CATS A, B, C, AND LNAV CAT C VISIBILITY 1/2 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	202/30 CW 022/30 (NOPT)	202/10 CW 022/10	3800
2.	202/10 CW 022/10	IGIDY (IF/IAF) (FB)	3300
3.	022/30 CW 112/30	JKALL (IAF) (FB)	3800
4.	112/30 CW 202/30	HORPU (IAF) (FB)	3400

QUALITY  
4  
CHECKED

CITY AND STATE  
HARVEY, ND

ELEVATION: 1607 TDZE: 1607  
AIRPORT NAME:  
HARVEY MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 29, ORIG-A  
28 JUL 2011

SUP:  
AMDT: ORIG  
DATED: 09/23/2010

# RNAV STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY  
4  
CHECKED

CITY AND STATE HARVEY, ND	ELEVATION: 1607 AIRPORT NAME: HARVEY MUNI	TDZE: 1607	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 29, ORIG-A 28 JUL 2011	SUP:	
					AMDT:	ORIG
					DATED:	09/23/2010