

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM			TO			COURSE AND DISTANCE			ALTITUDE			MAP: MVC VORTAC CLIMBING LEFT TURN TO 2000 IN MVC VORTAC HOLDING PATTERN. ADDITIONAL FLIGHT DATA: HOLD S, LT, 019.00 INBOUND. CHART FAS OBST: 503 TREE 312709N/0872127W CHART FAS OBST: 537 TANK 312421N/0872225W CHART A-292. FAC CROSSES RWY C/L EXTENDED 3183 FROM THLD.					
1. PT <u>R</u> SIDE OF COURSE <u>199.00</u> OUTBOUND <u>2000</u> FT WITHIN <u>10</u> MILES OF <u>MVC VORTAC</u> (IAF) 2. _____ 3. FAC <u>019.00</u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT <u>FONGU/MVC 2.04 DME 900*</u> 8. MSA FROM: <u>MVC VORTAC 2000</u>														MAG VAR: 4E		EPOCH YEAR: 1965	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		<input checked="" type="checkbox"/> X					
CATEGORY ==>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-3	900	1	488	900	1	488	900	1 3/8	488	900	1 3/8	488					
CIRCLING	900	1	481	900	1	481	920	1 1/2	501	980	2	561					
FONGU FIX MINIMUMS																	
S-3	820	1	408	820	1	408	820	1 1/8	408	820	1 1/8	408					
CIRCLING	840	1	421	880	1	461	920	1 1/2	501	980	2	561					
NOTES: CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE EVERGREEN ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET AND S-3 CATS C/D VISIBILITY 1/4 MILE AND FONGU FIX MINIMUMS INCREASE S-3 CATS C/D VISIBILITY 1/4 MILE. *960 WHEN USING EVERGREEN ALTIMETER SETTING. (SEE FORM 8260-10)																	
CITY AND STATE MONROEVILLE, AL				ELEVATION: 419 THRE: 412 AIRPORT NAME: MONROE COUNTY				FACILITY IDENTIFIER: MVC		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 3, AMDT 10 10 JANUARY 2013				SUP AMDT 9 DATE 12/20/2007			

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):**CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.****CHART NOTE: RWY 03 STRAIGHT-IN AND CIRCLING AND CIRCLING RWY 21 NA AT NIGHT.**

QUALITY
4
CHECKED

CITY AND STATE

MONROEVILLE, AL

ELEVATION: 419

THRE: 412

AIRPORT NAME:

MONROE COUNTY

FACILITY
IDENTIFIER:

MVC

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 3, AMDT 10

10 JANUARY 2013

SUP:

AMDT:

9

DATED:

12/20/2007