

**Federal Aviation
Administration**

Transmittal Letter 18-23

September 21, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
8-Nov-18	NY	Massena	Massena Intl- Richards Field	8/2410	9/12/18	ILS OR LOC RWY 5, Amdt 3A

AIRAC Date: 8 NOVEMBER 2018

FDC **8/2410** MSS IAP MASSENA INTL-RICHARDS FIELD, Massena, NY. ILS OR LOC RWY 5, AMDT 3A... CHART NOTE: CIRCLING RWY 9, 23, 27 NA AT NIGHT. DELETE NOTE: NIGHT LANDING: RWY 9 NA. S-LOC 5 CAT C VIS 1 3/4 SM. CIRCLING CAT C VIS 1 3/4 SM. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NA. EQUIPMENT REQUIREMENTS NOTE: ADF REQUIRED. DELETE NOTE: ADF REQUIRED. EQUIPMENT REQUIREMENTS NOTE: ADF AND RADAR REQUIRED FOR PROCEDURE ENTRY. DELETE PLANVIEW NOTE: ADF AND RADAR REQUIRED. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SARANAC LAKE ALTIMETER SETTING AND INCREASE ALL DA 481 FEET AND ALL MDA 500 FEET; INCREASE S-ILS ALL CATS VISIBILITY 1 3/4 MILES AND S-LOC CAT A VISIBILITY 1/4 MILE, CAT B 1/2 MILE, CAT C 1 1/2 MILES AND CAT D 1 1/4 MILES; INCREASE CIRCLING CAT A VISIBILITY 1/2 MILE, CAT B 3/4 MILE, CAT C 1 1/4 MILES AND CAT D 1/2 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE POTSDAM ALTIMETER SETTING AND INCREASE ALL DAS 73 FEET AND ALL MDAS 80 FEET; INCREASE S-ILS ALL CATS VISIBILITY 1/8 SM, S-LOC CAT C VISIBILITY 1/8 SM AND INCREASE CIRCLING CAT C VISIBILITY 1/8 SM, AND CAT D 1/4 SM. THIS IS ILS OR LOC RWY 5, AMDT 3B. 1808201351-PERM