

**FEDERAL AVIATION ADMINISTRATION**  
**FLIGHT STANDARDS SERVICE**  
**NDB STANDARD INSTRUMENT APPROACH PROCEDURE**  
**TITLE 14 CFR PART 97.27**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> NEW CASTLE HENRY COUNTY MARLATT FIELD	<u>AIRPORT ID</u> KUWL	<u>PROCEDURE NAME</u> NDB RWY 10	<u>ORIGINAL/AMENDMENT</u> ORIG-B	<u>CITY</u> NEW CASTLE	<u>STATE</u> IN
<u>AIRPORT ELEVATION</u> 1090	<u>TDZE</u> 1089	<u>SUPERSEDED</u> NDB RWY 10	<u>ORIGINAL/AMENDMENT</u> ORIG-A	<u>DATED</u> 11/08/2018	<u>MAG VAR</u> 6W
<u>FACILITY</u> UWL	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 25 APRIL 2019	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>	<u>EPOCH YEAR</u> 2020

**TERMINAL ROUTES**

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>

**MISSED APPROACH**

**MAP:**

UWL NDB

**MISSED APPROACH INSTRUCTIONS:**

CLIMB TO 2700 THEN RIGHT TURN DIRECT UWL NDB AND HOLD.

**ALTERNATE MISSED APPROACH INSTRUCTIONS:**

**PROFILE:**

1. PT L SIDE OF COURSE 266.62 OUTBOUND 2700 FT WITHIN 10 MILES OF UWL NDB (IAF)
- 2.
3. FAC: 086.62 FAF: DIST FAF TO MAP: DIST FAF TO THLD:
4. MIN ALT:
8. MSA FROM: UWL NDB 2900

**EQUIPMENT REQUIREMENTS NOTES:**

RADAR REQUIRED FOR PROCEDURE ENTRY.

**NOTES:**

CHART NOTE: RWY 10 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

CHART NOTE: USE ANDERSON ALTIMETER SETTING; WHEN NOT RECEIVED, USE MUNCIE ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET; INCREASE S-10 CAT C/D VISIBILITY 1/8 SM.

**ADDITIONAL FLIGHT DATA:**

CHART ANDERSON MUNI-DARLINGTON FIELD AWOS-3.  
CHART CIRCLING ICON.  
CHART FAS OBST: 1330 AAO 395027N/0852511W.  
FAC CROSSES RWY C/L EXTENDED 3002 FT FROM THLD.  
HOLD W, RT, 086.62 INBOUND



ALTERNATE: NA ☒

<u>CATEGORY:</u>	<u>A</u>			<u>B</u>			<u>C</u>			<u>D</u>			<u>E</u>		
<u>FINAL TYPE</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>
S-10	1760	1	671	1760	1	671	1760	1 7/8	671	1760	1 7/8	671			
CIRCLING	1760	1	670	1760	1	670	1780	2	690	1780	2 1/4	690			

**TITLE**  
MANAGER