

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

**PREVIOUSLY PUBLISHED IN
NFDD 205**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
KERMIT	THREE	KER3.KER	TWO	05/24/2018	03 JAN 2019

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

DP ROUTE DESCRIPTION:

CHARLOTTE/DOUGLAS INTL: RWY 5: CLIMB HEADING 055.47 TO 1700 BEFORE TURNING RIGHT, THENCE ... **RWY 18R:** CLIMBING RIGHT TURN HEADING 200.00, THENCE ... **RWY 18C:** CLIMB HEADING 182.96, THENCE ... **RWY 18L:** CLIMB HEADING 182.97, THENCE ... **RWY 23:** CLIMB HEADING 235.48, THENCE ... **RWY 36L:** CLIMB HEADING 002.96 TO 1800 THEN LEFT TURN HEADING 315, THENCE ... **RWY 36C:** CLIMB HEADING 002.98 TO 1400 THEN LEFT TURN HEADING 330, THENCE ... **RWY 36R:** CLIMBING RIGHT TURN HEADING 025.00, THENCE ...
... ON RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 8000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

CONCORD-PADGETT RGNL: RWY 2: CLIMB HEADING 016.46 TO 2200, THENCE ... **RWY 20:** CLIMBING LEFT TURN HEADING 150 TO 2400, THENCE... ON RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

GASTONIA MUNI: RWY 3: CLIMB HEADING 049.34 TO 2700 BEFORE TURNING LEFT, THENCE ... **RWY 21:** CLIMB HEADING 214.33 TO 1600 BEFORE PROCEEDING NORTH, THENCE ... ON RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

CHARLOTTE-MONROE EXECUTIVE: RWY 5: CLIMB HEADING 052.98, THENCE ... **RWY 23:** CLIMB HEADING 232.99, THENCE... ON RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

ROCK HILL/YORK CO/BRYANT FIELD: RWY 2: CLIMB HEADING 016.23, THENCE... **RWY 20:** CLIMB HEADING 196.23, THENCE... ON RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

LINCOLNTON-LINCOLN COUNTY RGNL: RWY 5: CLIMB HEADING 063.15 TO 2000 BEFORE PROCEEDING ON COURSE, THENCE ... **RWY 23:** CLIMB HEADING 233.15 TO 2800 BEFORE TURNING LEFT, THENCE... ON RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

LANCASTER COUNTY-MC WHIRTER FIELD: RWY 6: CLIMB HEADING 065.51, THENCE ... **RWY 24:** CLIMB HEADING 245.52, THENCE.... ON RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

STANLY COUNTY: RWY 4R: CLIMB HEADING 043.18, THENCE... **RWY 22L:** CLIMB HEADING 223.19, THENCE.... ON RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

MID-CAROLINA RGNL: RWY 2: CLIMB HEADING 021.99, THENCE ... **RWY 20:** CLIMB HEADING 201.99 TO 1700 BEFORE TURNING RIGHT, THENCE.... ON RADAR VECTORS TO INTERCEPT FILED/ASSIGNED TRANSITION OR ENROUTE FIX/NAVAID. MAINTAIN 3000, EXPECT FILED ALTITUDE/FLIGHT LEVEL 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
JOTTA	KER3.JOTTA	CLT VOR/DME	JOTTA	010.76 (CLT R-011)	49.64	6000	3400	
NALEY	KER3.NALEY	CLT VOR/DME	JOTTA	010.76 (CLT R-011)	49.64	6000	3400	
		JOTTA	NALEY	010.76 (CLT R-011)	20.35	8000	4000	
MERIL	KER3.MERIL	CLT VOR/DME	MERIL	075.77 (CLT R-076)	78.64	8000	4100	

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

DP NAME			NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER		DATED	EFFECTIVE DATE
KERMIT			THREE	KER3.KER	TWO		05/24/2018	03 JAN 2019
LILLS	KER3.LILLS	CLT VOR/DME	LILLS	111.58 (CLT R-112)	52.58	9000	2700	
ANDYS	KER3.ANDYS	CLT VOR/DME	ANDYS	196.00 (CLT R-196)	50.00	8000	2300	
TREAL	KER3.TREAL	CLT VOR/DME	ANDYS	196.00 (CLT R-196)	50.00	8000	2300	
		ANDYS	TREAL	196.00 (CLTR-196)	79.33	18000	2100	
DEBIE	KER3.DEBIE	CLT VOR/DME	DEBIE	255.00 (CLT R-255)	45.00	11000	2700	
HAMLN	KER3.HAMLN	CLT VOR/DME	WALUT	175.19 (CLT R-175)	31.83	5000	2200	
		WALUT	HAMLN	175.19 (CLT R-175)	18.70	5000	2000	
NEANO	KER3.NEANO	CLT VOR/DME	BOBZY	274.71 (CLT R-275)	33.56	8000	2900	
		BOBZY	NEANO	249.85 (ODF R-070)	18.89	8000	3600	

PROCEDURAL DATA NOTES:**NOTE: (CHARLOTTE/DOUGLAS INTL ONLY):** FOR TURBOJET AIRCRAFT REQUESTING AT OR ABOVE 11000.**NOTE: (ALL OTHER AIRPORTS):** FOR TURBOJET AIRCRAFT ONLY.**NOTE:** RADAR AND DME REQUIRED.**NOTE: (CHARLOTTE/DOUGLAS INTL ONLY):** ACCELERATE TO 250K, IF UNABLE ADVISE ATC. UPON REACHING 10000 MSL, ACCELERATE TO AND MAINTAIN 280K, IF UNABLE ADVISE ATC.**NOTE: (ALL OTHER AIRPORTS):** UPON REACHING 10000 MSL, ACCELERATE TO AND MAINTAIN 280K, IF UNABLE ADVISE ATC.**NOTE: (CHARLOTTE/DOUGLAS INTL ONLY):** TRANSPONDER CODE WILL BE ISSUED VIA PDC OR CHARLOTTE CLEARANCE DELIVERY.**NOTE: (CONCORD-PADGETT RGNL ONLY):** TRANSPONDER CODE WILL BE ISSUED VIA CONCORD ATCT OR CHARLOTTE CLEARANCE DELIVERY.**NOTE: (GASTONIA MUNI, CHARLOTTE-MONROE EXECUTIVE, ROCK HILL/YORK CO/BRYANT FIELD, LINCOLNTON-LINCOLN COUNTY RGNL, LANCASTER COUNTY-MC WHIRTER FIELD, STANLY COUNTY, MID-CAROLINA RGNL ONLY):** TRANSPONDER CODE WILL BE ISSUED VIA CHARLOTTE CLEARANCE DELIVERY.**TAKEOFF MINIMUMS:****CHARLOTTE /DOUGLAS INTL****RWY 5, 18C, 18L, 18R, 23, 36C, 36L, 36R, STANDARD.****CONCORD-PADGETT RGNL****RWY 2, STANDARD. RWY 20,** 300-1 3/4 OR STANDARD WITH MINIMUM CLIMB OF 204 FT PER NM TO 1000. OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT PER NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1200 FT PRIOR TO DER.**GASTONIA MUNI****RWY 3, 21, STANDARD.****CHARLOTTE-MONROE EXECUTIVE****RWY 5, 23, STANDARD.**

QUALITY
23
CHECKED

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
KERMIT	THREE	KER3.KER	TWO	05/24/2018	03 JAN 2019

LINCOLN-TON-LINCOLN COUNTY RGNL
RWY 5, 23, STANDARD.

LANCASTER COUNTY-MC WHIRTER FIELD
RWY 6, 24, STANDARD.

STANLY COUNTY
RWY 4L, 22R, NA
RWY 22L, STANDARD.
RWY 4R, 300-1 1/2 OR STANDARD WITH MINIMUM CLIMB OF 276 FT PER NM TO 1000.

MID-CAROLINA RGNL
RWY 2, STANDARD.
RWY 20, 400-2 3/4 OR STANDARD WITH MINIMUM CLIMB OF 205 FT PER NM TO 1300, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT PER NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1200 FT PRIOR TO DER.

ROCK HILL/YORK CO/BRYANT FIELD
RWY 2, 20 STANDARD.

TAKEOFF OBSTACLES NOTES:
SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
KERMIT	THREE	KER3.KER	TWO	05/24/2018	03 JAN 2019

CONTROLLING OBSTACLES:**CHARLOTTE/DOUGLAS INTL****RWY 5:** 1634 FT MSL BUILDING 351339.00N/0805032.00W (ROUTE DEVELOPMENT).**RWY 36C:** 2749 FT MSL BUILDING 352145.00N/0810918.00W (ROUTE DEVELOPMENT).**RWY 36L:** 2749 FT MSL BUILDING 352145.00N/0810918.00W (ROUTE DEVELOPMENT).**CONCORD-PADGETT RGNL****RWY 2:** 2349 FT MSL TOWER 353157.00N/0804746.00W.**RWY 20:** 849 FT MSL TREES 352123.50N/0804317.20W. 2000 FT MSL TOWER 351602.00N/0804404.00W.**GASTONIA MUNI****RWY 3, 21:** 2754 FT MSL TOWER 352049.00N/0811014.00W (ROUTE DEVELOPMENT).**LINCOLNTON-LINCOLN COUNTY RGNL****RWY 5:** 2754 FT MSL TOWER 352049.00N/0811014.00W (ROUTE DEVELOPMENT).**RWY 23:** 2719 FT MSL TOWER 352151.00N/0811112.00W (ROUTE DEVELOPMENT).**STANLY COUNTY****RWY 4R:** 837 FT MSL TREE 352627.34N/0800808.17W (CLIMB GRADIENT).**MID-CAROLINA RGNL****RWY 20:** 1121 FT MSL TOWER 353613.00N/0803234.12W (CLIMB GRADIENT). 1848 FT MSL TOWER 353531.99N/0803743.98W (ROUTE DEVELOPMENT).**LOST COMMUNICATIONS PROCEDURES:****ADDITIONAL FLIGHT DATA:****CHART:** V37, JOTTA TO NALEY. **CHART:** ODF DME AT NEANO.**CHARLOTTE/DOUGLAS INTL - CHART:** TOP ALTITUDE 8000**CHART:** SOUTHEAST AND NORTHWEST DEPARTURE SECTORS WITH DASHED LINE EXTENDED THROUGH CLT VOR/DME FROM 055 DEGREES TO 235 DEGREES.**CONCORD-PADGETT RGNL - CHART:** TOP ALTITUDE 3000.**GASTONIA MUNI - CHART:** TOP ALTITUDE 3000.**CHARLOTTE-MONROE EXECUTIVE - CHART:** TOP ALTITUDE 3000.**LINCOLNTON-LINCOLN COUNTY RGNL - CHART:** TOP ALTITUDE 3000.**LANCASTER COUNTY-MC WHIRTER FIELD - CHART:** TOP ALTITUDE 3000.**STANLY COUNTY - CHART:** TOP ALTITUDE 3000.**MID-CAROLINA RGNL - CHART:** TOP ALTITUDE 3000.**ROCK HILL/YORK CO/BRYANT FIELD - CHART:** TOP ALTITUDE 3000.

QUALITY
23
CHECKED

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

DP NAME	NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
KERMIT	THREE	KER3.KER	TWO	05/24/2018	03 JAN 2019

AIRPORTS SERVED:

AIRPORT NAME	CITY	STATE
CHARLOTTE/DOUGLAS (KCLT)	CHARLOTTE	NC
CONCORD-PADGETT RGNL (KJQF)	CONCORD	NC
GASTONIA MUNI (KAKH)	GASTONIA	NC
CHARLOTTE-MONROE EXECUTIVE (KEQY)	MONROE	NC
LINCOLN-NTON-LINCOLN COUNTY RGNL (KIPJ)	LINCOLN-NTON	NC
LANCASTER COUNTY-MCWHIRTER FIELD (KLKR)	LANCASTER	SC
STANLY COUNTY (KVUJ)	ALBEMARLE	NC
MID-CAROLINA RGNL (KRUQ)	SALISBURY	NC
ROCK HILL/YORK COUNTY/BRYANT FIELD (KUZA)	ROCK HILL	SC

COMMUNICATIONS:
CHARLOTTE/DOUGLAS INTL: ATIS, CLNC DEL, GND CON, TOWER, DEP CON.
CONCORD-PADGETT RGNL: ATIS, CLNC DEL, GND CON, TOWER, UNICOM, DEP CON.
GASTONIA MUNI: ASOS, CLNC DEL, UNICOM, DEP CON.
CHARLOTTE-MONROE EXECUTIVE : ASOS, CLNC DEL, UNICOM, DEP CON.
ROCK HILL/YORK CO/BRYANT FIELD: ASOS, CLNC DEL, UNICOM, DEP CON.
LINCOLN-NTON-LINCOLN COUNTY RGNL: AWOS, CLNC DEL,(GCO), UNICOM, DEP CON.
LANCASTER COUNTY -MC WHIRTER FIELD: AWOS, GCO, UNICOM, DEP CON.
MID-CAROLINA RGNL: AWOS, CLNC DEL, UNICOM, DEP CON.
STANLY COUNTY: ATIS, CLNC DEL, GND CON, TOWER, UNICOM, DEP CON.

FIXES AND/OR NAVAIDS:

BZM VOR/DME, PSK VORTAC, RDU VORTAC,
ODF VORTAC

REMARKS:

ABBREVIATED AMENDMENT



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
KERMIT	THREE	KER3.KER	TWO	05/24/2018	03 JAN 2019

FLIGHT INSPECTED BY:**OFFICE SYMBOL:** **DATE:***Digitally signed by*

FLIGHT INSPECTION REVIEW NOT REQUIRED - PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, DEC 22, 2017.

DAVID DANNER

Oct 30, 2018

DEVELOPED BY: *Digitally signed by*
RUSS ROSLEWSKI **RUSSELL ROSLEWSKI**
Jul 30, 2018

OFFICE SYMBOL: **DATE:**

AJV-5421

07/30/2018

APPROVED BY: *Digitally signed by*
JULIE MORGAN **DAVID DANNER**
Oct 30, 2018

OFFICE SYMBOL: **DATE:**

AJV-5420

REQUIRED EFFECTIVE DATE: ROUTINE**COORDINATED WITH:**

<u>A4A</u>	<u>ALPA</u>	<u>AOPA</u>	<u>APA</u>	<u>HAI</u>	<u>NBAA</u>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

OTHER:

ATA, ZTL, CLT APP CON, CLT ATCT, JQF ATCT, VUJ ATCT, AMGR(S).

CHANGES - REASONS:

1. CHANGED AIRPORT NAME FROM CONCORD RGNL TO CONCORD-PADGETT RGNL - IDENTIFIED DURING 28-DAY REVIEW.
2. REMOVED TAKEOFF OBSTACLE NOTES AND REPLACED WITH NOTE TO SEE FORM 8260-15A - NO LONGER CHARTED ON SIDS.

10/25/2018: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 9/27/2018:

1. DP ROUTE DESCRIPTION, LANCASTER COUNTRY-MC WHIRTER FIELD, STANLY COUNTY AND MID-CAROLINA RGNL, CHANGED "EXPECT RADAR VECTORS" TO "ON RADAR VECTORS" TO MATCH PREVIOUS AMENDMENT.
2. ADDITIONAL FLIGHT DATA, CORRECTED SPELLING OF "CHARLOTTE/DOUGLAS INTL" AND "LINCOLNTON-LINCOLN COUNTY RGNL".

QUALITY
23
CHECKED