

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LP: RW18 LNAV: RW18					
LIT VORTAC		ALMOW (TF) (FO) (RNP 2.00)		350.53 / 15.42				2700		CLIMB TO 4000 DIRECT FEHXE AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4000.					
BIBBS (IAF)		ALMOW (NOPT) (TF) (FB) (RNP 1.00)		095.70 / 19.65				2700							
DUMPI (IAF)		ALMOW (NOPT) (TF) (FB) (RNP 1.00)		268.38 / 13.36				2700							
ALMOW (IF/IAF)		RUZAL (TF) (FB) (RNP 1.00)		181.51 / 6.50				1900							
RUZAL (FAF)		ZEDEB/2.30 NM TO RW18 (TF) (FB) (RNP 0.30)		181.51 / 2.70				1900		ADDITIONAL FLIGHT DATA: HOLD S, RT, 001.51 INBOUND. CHART FAS OBST: 558 TOWER 344621N/0921445W, 466 ELEVATOR 344547N/0921416W. CHART R-2403A AND R-2403B. CHART VDP AT 1.29 NM TO RW18. WAAS CHANNEL # 45624 REFERENCE PATH ID: W18A CHART CIRCLING ICON. RUZAL TO RW18: 3.00/50. 749 AAO 344937N/0921527W CHART: ASR LTP HAE: 52.3 M					
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 0E EPOCH YEAR: 2020					
2. HOLD N ALMOW, RT, 181.51 INBOUND, 2700 FT. IN LIEU OF PT (IAF)															
3. FAC: 181.51 FAF: RUZAL DIST FAF TO MAP: 5.00 THLD: 5.00															
4. MIN. ALT: ALMOW 2700, RUZAL 1900, ZEDEB/2.30 NM TO RW18 1040															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR															
8. MSA FROM: RW18 3300															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	720	1	461	720	1	461	720	1 3/8	461	720	1 3/8	461			
LNAV MDA	820	1	561	820	1	561	820	1 5/8	561	820	1 5/8	561			
CIRCLING	820	1	554	1000	1	734	1180	2 3/4	914	1180	3	914			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. @ CAT C 1000-2 3/4, CAT D 1000-3 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON LIT VORTAC AIRWAY RADIALS 273 CW 059. CHART NOTE: PROCEDURE NOT AUTHORIZED WHEN RESTRICTED AREAS R-2403A/B IN EFFECT. CHART NOTE: RWY 18 HELICOPTER VISIBLTY REDUCTION BELOW 3/4 SM NOT AUTHORIZED															
CITY AND STATE LITTLE ROCK, AR		ELEVATION: 266 TDZE: 259 AIRPORT NAME: BILL AND HILLARY CLINTON NATIONAL/ADAMS FIELD		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 1E 19 JULY 2018				SUP: AMDT: 1D DATED 03/05/2015					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
ZEDEB/2.30 NM TO RW18	RW18 (MAP) (TF) (FO) (RNP 0.30)	181.51 / 2.30	
RW18 (MAP)	666 MSL (CA)	181.51	
666 MSL	FEHXE (DF) (FO) (RNP 1.00)		

QUALITY
4
CHECKED

CITY AND STATE
LITTLE ROCK, AR

ELEVATION: 266 TDZE: 259
AIRPORT NAME:
BILL AND HILLARY CLINTON NATIONAL/ADAMS
FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 18, AMDT 1E
19 JULY 2018

SUP:
AMDT: 1D
DATED: 03/05/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KLIT
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	344423.2440N
LTP/FTP LONGITUDE	0921417.1390W
LTP/FTP ELLIPSOIDAL HEIGHT	+00523
FPAP LATITUDE	344254.0200N
FPAP LONGITUDE	0921419.9900W
THRESHOLD CROSSING HEIGHT (TCH)	00050.1
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0856
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
 <u>CRC REMAINDER</u>	 6E651F25

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00789
FPAP ORTHOMETRIC HEIGHT	+00789

QUALITY
4
CHECKED

CITY AND STATE LITTLE ROCK, AR	ELEVATION: 266 AIRPORT NAME: BILL AND HILLARY CLINTON NATIONAL/ADAMS FIELD	TDZE: 259 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 1E 19 JULY 2018	SUP:
				AMDT: 1D
				DATED: 03/05/2015