

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
VOR STANDARD INSTRUMENT APPROACH PROCEDURE**

TITLE 14 CFR PART 97.23

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> SAN GABRIEL VALLEY	<u>AIRPORT ID</u> KEMT	<u>PROCEDURE NAME</u> VOR-A	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> EL MONTE	<u>STATE</u> CA	
<u>AIRPORT ELEVATION</u> 296	<u>TDZE</u>	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u>	<u>DATED</u>	<u>MAG VAR</u> 15E	<u>EPOCH YEAR</u> 1975
<u>FACILITY</u> POM	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 13 SEPTEMBER 2018	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
PDZ VORTAC	IAF	POM VORTAC	NOPT				291.85	16.01	4000
PRADO INT/POM 9.30 DME	IAF	POM VORTAC	NOPT				343.99	9.30	4000
POM VORTAC	IF/IAF	FLYIN INT/POM 3.07 DME					257.87	3.07 (POM R-258)	3700
FLYIN INT/POM 3.07 DME		SELAW INT/POM 6.30 DME					257.87	3.23 (POM R-258)	3000

MISSED APPROACH

MAP:

5.93 NM AFTER SELAW INT/POM 6.30 DME OR AT CFVFM.

MISSED APPROACH INSTRUCTIONS:

CLIMBING LEFT TURN TO 2500 ON HEADING 070 AND PDZ VORTAC R-278 TO ADAMM INT/PDZ 15.49 DME THEN CONTINUE CLIMB TO 4000 TO PDZ VORTAC.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

- 1. PT** **SIDE OF COURSE** **OUTBOUND** **FT WITHIN** **MILES OF (IAF)**
- 2.** HOLD E POMONA VORTAC, LT, 292.00 INBOUND, 4000 FT. IN LIEU OF PT (IAF), MAX 6000.
- 3. FAC:** 257.87 **FAF:** SELAW INT/POM 6.30 DME **DIST FAF TO MAP:** 5.93 **DIST FAF TO THLD:**
- 4. MIN ALT:** POM VORTAC 4000, FLYIN INT/POM 3.07 DME 3700, SELAW INT/POM 6.30 DME 3000
- 8. MSA FROM:** POM VORTAC 075-190 6900, 190-280 7700, 280-075 11300

EQUIPMENT REQUIREMENTS NOTES:

NOTES:

CHART NOTE: CIRCLING RWY 1 NA AT NIGHT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ONTARIO INTL ALTIMETER SETTING AND INCREASE ALL MDA 160 FEET.



ADDITIONAL FLIGHT DATA:

FAC CROSSES RWY 382 FEET S OF RWY 19 DISPLACED THRESHOLD.
CHART CIRCLING ICON.
FAS OBST: 780 AAO 340601N/1175312W.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ LOC: NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
CIRCLING	1280	1 1/4	984	1280	1 1/2	984	1280	3	984	1320	3	1024			

CHANGES - REASONS

COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZLA, SOCAL APP CON, AMGR

FLIGHT CHECKED BY

DANIEL C FAVORITE

DEVELOPED BY

LONNIE EVERHART (THERON CYRUS)

APPROVED BY

LONNIE EVERHART

Digitally signed by

ADOLFO D URRUTIA

Jul 10, 2018

Digitally signed by

ADOLFO D URRUTIA

Jul 10, 2018

OFFICE

FICO

OFFICE

AJV-5400

OFFICE

AJV-5400

DATE

7/6/18

DATE

03/30/2018

DATE

TITLE

MANAGER

