

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
WLKKR	FOUR	WLKKR4.WLKKR	THREE	05/24/2018	05DEC2019
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:

RWY 16R: CLIMB ON HEADING 163.51 TO 1303, THEN CLIMB DIRECT PPRRY, THEN ON HEADING 210, OR AS ASSIGNED BY ATC, THEN ON VECTORS TO CROSS LUVVY AT OR ABOVE 6000 THEN ON TRACK 331.19 TO CROSS WLKKR AT OR ABOVE 8000 THENCE...

...ON (TRANSITION) MAINTAIN FL230. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
COREZ	WLKKR4.COREZ	WLKKR	OROSZ	TRACK 325.35	3.48	8000	5300	OROSZ AT/ABOVE 9000
		OROSZ	BRRKK	TRACK 317.70	10.00	9000	6300	
		BRRKK	SHORS	TRACK 317.67	15.60	12000	10300	
		SHORS	MDWAY	TRACK 317.53	12.49	12000	10300	
		MDWAY	COREZ	TRACK 317.48	40.49	14000	8200	
CSTRO	WLKKR4.CSTRO	WLKKR	OROSZ	TRACK 325.35	3.48	8000	5300	OROSZ AT/ABOVE 9000
		OROSZ	HEYJO	TRACK 338.83	17.77	9000	8000	
		HEYJO	CSTRO	TRACK 318.52	50.20	14000	8000	
OROSZ	WLKKR4.OROSZ	WLKKR	OROSZ	TRACK 325.35	3.48	8000	5300	OROSZ AT/ABOVE 9000

PROCEDURAL DATA NOTES:

NOTE: RADAR REQUIRED

NOTE: RNAV 1

NOTE: DME/DME/IRU OR GPS REQUIRED

NOTE: MAINTAIN AT OR BELOW 250 KIAS UNLESS OTHERWISE DIRECTED BY ATC

NOTE: TURBOJET ONLY

NOTE: CROSS DER/VNY VOR/DME 1.5 DME SOUTH AT OR BELOW 1750

NOTE: OROSZ TRANSITION FOR BAKERSFIELD AREA ARRIVALS ONLY.

TAKEOFF MINIMUMS:

RWY 16L; RWY 34L/R - NA, ATC

RWY 16R: STANDARD WITH A MINIMUM CLIMB OF 450 FT/NM TO 2600

QUALITY
3
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
WLKKR	FOUR	WLKKR4.WLKKR	THREE	05/24/2018	05DEC2019

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

RWY 16R, 2159 FT MSL AAO 340743.75N/1183045.87W

LOST COMMUNICATIONS PROCEDURES:**ADDITIONAL FLIGHT DATA:**

CHART: TOP ALTITUDE FL230

REFERENCE MAG VAR: KVNY 12E EPOCH YR: 2020

DME/DME ASSESSMENT SAT: RNP (2.0)

DO NOT CHART MOCAS.

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
VAN NUYS (KVNY)	VAN NUYS	CA

COMMUNICATIONS:

ATIS, CLNC DEL, GND CON, SOCAL APP CON

FIXES AND/OR NAVAIDS:**REMARKS:**

1. WAIVER ON FILE AUTHORIZING AT OR BELOW 1750 CROSSING RESTRICTON AT DER THAT PROVIDES LESS THAN 1000 FEET OF ROC ABOVE HIGHEST OBSTACLE.

FLIGHT INSPECTED BY:PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018, SUBJECT: FLIGHT INSPECTION
REVIEW NOT REQUIRED.**OFFICE SYMBOL:***Digitally signed by***WARDELL HENNING**

Jul 30, 2019

DATE:**OFFICE SYMBOL:**

AJV-A432

DATE:

06/06/2019

DEVELOPED BY:

WARDELL HENNING (THOR CORNELL)

*Digitally signed by***WARDELL HENNING**

Jul 30, 2019

APPROVED BY:

LONNIE EVERHART

*Digitally signed by***WARDELL HENNING**

Jul 30, 2019

OFFICE SYMBOL:

AJV-A430

DATE:**REQUIRED EFFECTIVE DATE:**

ROUTINE

COORDINATED WITH:

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
WLKKR	FOUR	WLKKR4.WLKKR	THREE	05/24/2018	05DEC2019
<u>A4A</u>	<u>ALPA</u>	<u>AOPA</u>	<u>APA</u>	<u>HAI</u>	<u>NBAA</u>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

OTHER:

CHANGES - REASONS:

1. CHANGED DP ROUTE DESCRIPTION FROM CLIMB HEADING 163.51 TO 1303, THEN DIRECT PPRRY, TO CLIMB ON HEADING 163.51 TO 1303, THEN CLIMB DIRECT PPRRY. - PER 8260.46G APDX D SECTION D SECTION 1, 8A.
2. REMOVED TAKEOFF OBSTACLE NOTES AND ADDED "SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP). - PER 8260.46G, APDX D, SECT 2, PARA 7.
3. ADDED CHART NOTE: OROSZ TRANSITION FOR BAKERSFIELD AREA ARRIVALS ONLY. - PER PUBLISHED DATA.
4. CHANGED MOCA FROM WLKKR TO OROSZ ON CSTRO TRANSITION FROM 5000 TO 5300. - PER PUBLISHED DATA.
5. CHANGED VA ALTITUDE FROM RW16R TO PPRRY FROM 1303 MSL TO AT/ABOVE 1303 MSL ON THE 8260-15C FORM. - PER 8260.46G, APDX E, SECT 1, PARA 3E, NOTE.

QUALITY
3
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
WLKKR		FOUR		WLKKR4.WLKKR		THREE		05/24/2018	05DEC2019
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW 16R (AER)*	341253.96N/1182927.13W	N	-	-	-	-			*DISPL THLD (1431.642 FT)
AT/ABOVE 1303 MSL	-	-	-	VA	175.51	-			CG 450 FPNM TO 2600
PPRRY	341034.88N/1182913.99W	Y	FO	DF	-	-			
-	-	-	-	VM	222.00	-			
LUVVY	341637.75N/1183643.92W	Y	-	IF	-	-	AT/ABOVE 6000		
WLKKR	342222.95N/1183849.68W	Y	FB	TF	343.19	6.00	AT/ABOVE 8000		
WLKKR	342222.95N/1183849.68W	Y	-	IF	-	-	AT/ABOVE 8000	WLKKR4.COREZ	
OROSZ	342536.18N/1184027.01W	Y	FB	TF	337.35	3.48	AT/ABOVE 9000		
BRRKK	343414.96N/1184633.55W	Y	FB	TF	329.70	10.00			
SHORS	344743.61N/1185607.37W	Y	FB	TF	329.67	15.60			
MDWAY	345830.50N/1190349.98W	Y	FB	TF	329.53	12.49			
COREZ	353324.00N/1192901.98W	Y	FB	TF	329.48	40.49			
WLKKR	342222.95N/1183849.68W	Y	-	IF	-	-	AT/ABOVE 8000	WLKKR4.CSTRO	
OROSZ	342536.18N/1184027.01W	Y	FB	TF	337.35	3.48	AT/ABOVE 9000		
HEYJO	344310.33N/1184353.04W	Y	FB	TF	350.83	17.77			
CSTRO	352652.66N/1191407.00W	Y	FB	TF	330.52	50.20			
WLKKR	342222.95N/1183849.68W	Y	-	IF	-	-	AT/ABOVE 8000	WLKKR4.OROSZ	
OROSZ	342536.18N/1184027.01W	Y	FB	TF	337.35	3.48	AT/ABOVE 9000		

QUALITY
3
CHECKED