

**Federal Aviation
Administration**

Transmittal Letter 18-23

September 21, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
8-Nov-18	VA	Charlottesville	Charlottesville- Albemarle	8/1832	9/11/18	ILS OR LOC RWY 3, Amdt 1

AIRAC Date: 8 NOVEMBER 2018

FDC **8/1832** CHO IAP CHARLOTTESVILLE-ALBEMARLE, Charlottesville, VA. ILS OR LOC RWY 3, AMDT 1... JITIV FIX MINIMUMS S-LOC 3 MDA 1000/HAT 360 ALL CATS. JITIV FIX MINIMUMS CIRCLING CAT A MDA 1100/HAA 460. CHART NOTE: FOR INOP ALS WHEN USING ORANGE ALTIMETER SETTING INCREASE S-ILS 3 ALL CATS VISIBILITY TO 7/8, S-LOC 3 CATS C, D VISIBILITY TO 2 MILES, AND S-LOC 3 JITIV FIX MINIMUMS CAT C, D VISIBILITY TO 1 1/8 MILE. DELETE NOTE: FOR INOP MALSR WHEN USING ORANGE ALTIMETER SETTING, INCREASE S-ILS 3 ALL CATS VISIBILITY TO 7/8 MILE, S-LOC 3 CATS C/D VISIBILITY TO 2 MILES, AND S-LOC 3 JITIV FIX MINIMUMS CATS C/D VISIBILITY TO 1 1/8 MILE. THIS IS ILS OR LOC RWY 3, AMDT 1A. 1807231523-PERM