

**Federal Aviation  
Administration**

**Transmittal Letter 19-05**

**January 11, 2019**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
28-Feb-19	MS	Tunica	Tunica Muni	8/3448	1/8/19	RNAV (GPS) RWY 17, Amdt 3

**AIRAC Date: 28 FEBRUARY 2019**

FDC **8/3448** UTA IAP TUNICA MUNI, Tunica, MS. RNAV (GPS) RWY 17, AMDT 3...  
LPV VIS 3/4 ALL CATS. LNAV VIS CATS C/D 1 1/8. CHART NOTE: FOR  
INOPERATIVE ALS, INCREASE LNAV/VNAV VIS ALL CATS TO 7/8 SM, AND LNAV  
CATS C, D VIS TO 1 3/8 SM. CHART NOTE: WHEN LOCAL ALTIMETER SETTING  
NOT RECEIVED, USE MEMPHIS ALTIMETER SETTING AND INCREASE LPV DA  
TO 480, LNAV/VNAV DA TO 557, AND ALL MDA 100 FEET, INCREASE LNAV/VNAV  
VIS ALL CATS TO 1 SM AND CIRCLING CAT C VIS TO 1 3/4 SM. CHART NOTE:  
FOR INOPERATIVE ALS WHEN USING MEMPHIS ALTIMETER SETTING,  
INCREASE LPV ALL CATS VISIBILITY TO 7/ 8 SM, LNAV/ VNAV ALL CATS  
VISIBILITY TO 1 SM, LNAV CATS C/D VISIBILITY TO 1 5/8 SM. PBN  
REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA.  
DELETE NOTE: FOR INOP ODALS, INCREASE LPV ALL CATS VISIBILITY TO 3/4  
MILE, LNAV/VNAV ALL CATS TO 7/8 MILE, AND LNAV CAT D VISIBILITY TO 1 3/8  
MILE. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE  
MEMPHIS ALTIMETER SETTING AND INCREASE LPV DA TO 480, LNAV/VNAV DA  
TO 557, AND ALL MDA 100 FEET; INCREASE LPV ALL CATS VISIBILITY 1/8 MILE,  
INCREASE LNAV/VNAV ALL CATS VISIBILITY 3/8 MILE, INCREASE LNAV CATS C  
AND D AND CIRCLING CAT C VISIBILITY 1/4 MILE. DELETE NOTE: FOR INOP  
MALSR WHEN USING MEMPHIS ALTIMETER SETTING, INCREASE LPV ALL CATS  
VISIBILITY TO 7/8 MILE, LNAV/VNAVALL CATS VISIBILITY TO 1 1/4 MILE, LNAV

CAT D VISIBILITY TO 2 MILE. THIS IS RNAV (GPS) RWY 17, AMDT 3A.  
1812192150-PERM