

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
NDB STANDARD INSTRUMENT APPROACH PROCEDURE																				
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27																				
TERMINAL ROUTES										MISSED APPROACH										
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: 8.01 MILES AFTER SN NDB OR AT FIPMU/I-GSN 9.86 DME FIX									
WILLE/UNZ 98.00 DME			SN NDB			065.79 / 21.66			2800		CLIMBING RIGHT TURN TO 2800 DIRECT SN NDB AND HOLD.									
HIRCH/UNZ 100.00 DME			SN NDB			348.04 / 19.55			2800											
										ADDITIONAL FLIGHT DATA: HOLD NE, RT, 216.24 INBOUND. CHART FAS OBST: 657 TREE 150224N/1453747E FAC CROSSES MID POINT OF RWY 8/26. CHART CIRCLING ICON. ** DME FROM I-GSN LOC/DME.										
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																				
2. HOLD NE SN NDB, RT, 216.24 INBOUND, 2800 FT. IN LIEU OF PT (IAF)																				
3. FAC 216.24 FAF SN NDB _____ DIST FAF TO MAP 8.01 THLD _____																				
4. MIN. ALT SN NDB 2800, UYHEW/I-GSN 6.58 DME 1060*																				
8. MSA FROM: SN NDB 2800										MAG VAR: 2E EPOCH YEAR: 1985										
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X										
CATEGORY =====>		A			B			C			D			E						
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA					
CIRCLING	1060	1	789	1060	1	789	1060	2 1/4	789	1060	2 1/2	789								
UYHEW FIX MINIMUMS**																				
CIRCLING	960	1	689	960	1	689	1000	2	729	1060	2 1/2	789								
NOTES:																				
CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE SAIPAN ALTIMETER SETTING AND INCREASE ALL MDA 40 FT, AND ALL CATS VISIBILITY 1/4 SM. INCREASE UYHEW FIX MINIMUMS CATS C AND D VISIBILITY 1/4 MILE.																				
*1100 WHEN USING SAIPAN ALTIMETER SETTING.																				
CITY AND STATE		ELEVATION: 271		TDZE:		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP								
TINIAN ISLAND, CQ		AIRPORT NAME:				SN		NDB-A, AMDT 3				AMDT 2								
		TINIAN INTL						10 NOVEMBER 2016				DATE 08/22/2013								