

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW05L CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 3000 DIRECT XUB VOR AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, LT, 176.00 INBOUND. CHART FAS OBST: 830 APRON LIGHT 394828N/0825656W DISTANCE TO THLD FROM 200 HATH: 0.45 NM. WAAS CHANNEL # 78022 REFERENCE PATH ID: W05B LTP HAE: 192.1 M											
TARTO	LAKDE (FB)	281.32 / 17.65	3000												
LAKDE (IAF)	HIGID (NOPT) (FB)	320.39 / 8.00	3000												
GAILL (IAF)	HIGID (NOPT) (FB)	077.48 / 14.09	3000												
HIGID (IF/IAF)	COLMU (FB)	050.19 / 7.20	2400												
COLMU (FAF)	ZOGAM/1.20 NM TO RW05L (FB)	050.26 / 3.83													
ZOGAM/1.20 NM TO RW05L (SEE FORM 8260-10)	RW05L (MAP) (FO)	050.30 / 1.20													
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SW HIGID, RT, 050.19 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 050.26 FAF: COLMU DIST FAF TO MAP: 5.03 THLD: 5.03 4. MIN. ALT: HIGID 3000, COLMU 2400, ZOGAM/1.20 NM TO RW05L 1200* 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: 2400 GS ALT AT: COLMU 2400 OM: MM: IM: 7. GS ANGLE: 3.00 TCH: 55.0 34:1 IS CLEAR 8. MSA FROM: RW05L 3100															
MINIMUMS				MAG VAR: 5W EPOCH YEAR: 1985											
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A		STANDARD @										
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	942	1/2	200	942	1/2	200	942	1/2	200	942	1/2	200			
LNAV/VNAV DA	992	1/2	250	992	1/2	250	992	1/2	250	992	1/2	250			
LNAV MDA	1080	1/2	338	1080	1/2	338	1080	1/2	338	1080	1/2	338			
CIRCLING	1180	1	436	1200	1	456	1200	1 1/2	456	1300	2	556			
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING PORT COLUMBUS INTL ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 39C (102F). CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 3/4 MILE. CHART NOTE: CIRCLING NA NW OF RWY 5L-23R. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 744 THRE: 742		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:		SUP:							
COLUMBUS, OH		AIRPORT NAME: RICKENBACKER INTL		RNAV		RNAV (GPS) RWY 5L, ORIG 25 AUG 2011		AMDT: NONE							
								DATED							